

SAFETY DATA SHEET

REVISION DATE: 09-26-2018

SUPERSEDES: 03-22-2018

SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER**PRODUCT INFORMATION**

PRODUCT: FOSTER 95-44 CARTRIDGE
PRODUCT DESCRIPTION: Sealant
INTENDED USE: Sealant
PRODUCT IDENTIFIER: 802436PM

COMPANY INFORMATION

H.B. Fuller Construction Products Inc.
 1105 S. Frontenac Street
 Aurora, IL 60504
 Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758
 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION**GHS Hazard Symbols:**

GHS Signal Word: Danger
GHS Classification: Carcinogenicity Category 1A; Flammable Liquid Category 3; Hazardous to the aquatic environment - Chronic Category 3
GHS Hazard Phrases: Flammable liquid and vapour.; May cause cancer.; Harmful to aquatic life with long lasting effects.
GHS Precautions:
Safety Precautions: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
First Aid Measures: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF exposed or concerned: Get medical advice/attention. In case of fire: Use water spray, foam, dry chemical or carbon dioxide to extinguish.
Storage: Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal: Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	PERCENT	Classification	Note
---------------	-------	---------	----------------	------

SAFETY DATA SHEET

Stoddard solvent	8052-41-3	10 - 30	Asp. Tox. 1; H304	Note P
Polybutene	9003-29-6	10 - 30	Aquatic Chronic 4; H413	
Fuller's earth	8031-18-3	5 - 10	Aquatic Chronic 2; H411 Acute Tox. 4; H302	* (see below)
Trimethylbenzene, 1,2,4-	95-63-6	1 - 5	Aquatic Chronic 2; H411 Acute Tox. 4; H332 Eye Irrit. 2; H319 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT SE 3; H335, H336	
Crystalline silica	14808-60-7	0.1 - 1	Carc. 1A; H350 STOT RE 1; H372	* (see below)
Dimethyldicocoammonium chloride: CAS:61789-77-3	61789-77-3	0.1 - 1	Aquatic Acute 1; H400 Acute Tox. 4; H302 Skin Corr. 1B; H314	
Cumene	98-82-8	0.1 - 1	Aquatic Chronic 2; H411 Asp. Tox. 1; H304 Acute Tox. 4; H302 Carc. 2; H351 Flam. Liq. 3; H226 STOT SE 3; H335, H336	

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains crystalline silica. As provided, and during normal use of this product, the crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

IF IN EYES: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention immediately. Drink two glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:

Use water spray, foam, dry chemical or carbon dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Vapors are heavier than air and can travel to a source of ignition and flash back.

SPECIAL FIRE FIGHTING INSTRUCTIONS:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS:

Carbon dioxide, Carbon monoxide Silicon dioxide

SECTION 6: ACCIDENTAL RELEASE MEASURES

SAFETY DATA SHEET

SPECIAL PROTECTION: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

METHODS FOR CLEAN-UP: Scrape up and place in disposal container. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: Avoid contacting and avoid breathing the material. Use only in a well ventilated area.
 Keep away from heat, sparks and flame.
 Wash thoroughly after handling.
 Keep container closed.
 Emptied container retains vapor and product residue.
 Observe all labeled precautions until container is cleaned.
 Drums of this material should be grounded when pouring.
DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.

Storage: Store in a cool, dry, ventilated location. Keep away from heat and flame. Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS:

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Stoddard solvent	Note P	100 ppm TWA	500 ppm TWA; 2900 mg/m ³ TWA
Calcium carbonate	* (see below)	No data available.	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)
Inorganic Filler	* (see below)	3 mg/m ³ TWA (respirable particulate matter)	Not established
Amorphous silica	* (see below)	No data available.	20 mppcf TWA; ((80)/(% SiO ₂)) mg/m ³ TWA)
Crystalline silica	* (see below)	0.025 mg/m ³ TWA (respirable particulate matter)	((250)/(%SiO ₂ + 5) mppcf TWA (respirable)); ((10)/(%SiO ₂ + 2) mg/m ³ TWA (respirable)); ((30)/(%SiO ₂ + 2) mg/m ³ TWA (total dust))
Cumene		50 ppm TWA	50 ppm TWA; 245 mg/m ³ TWA Skin absorption may potentially contribute to the overall exposure to this material.

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains crystalline silica. As provided, and during normal use of this product, the

SAFETY DATA SHEET

crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153.

ENGINEERING CONTROL METHODS:

VENTILATION:	Use local exhaust ventilation or other engineering controls to minimize exposures.
EYE PROTECTION:	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
SKIN PROTECTION:	Avoid skin contact by wearing chemically resistant gloves. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption so that the TLV is not invalidated.
GLOVES:	Nitrile
RESPIRATORY PROTECTION:	Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with organic vapor cartridge. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Semi-solid
COLOR:	Aluminum
ODOR:	Solvent
ODOR THRESHOLD:	Not established
pH:	Not established
FREEZING/MELTING POINT (deg. C):	Not established
BOILING POINT (deg. C):	Not established
FLASH POINT:	> 43°C; 109°F Pensky-Martens
EVAPORATION RATE:	Not established
FLAMMABILITY:	Not a flammable solid or gas
UPPER EXPLOSIVE LIMIT (% in air):	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
VAPOR PRESSURE (mm Hg):	Not established
VAPOR DENSITY:	Not established
WEIGHT PER GALLON (lbs.):	9.60
SPECIFIC GRAVITY:	1.150
SOLUBILITY:	Not established
OCTANOL/WATER COEFFICIENT:	Not established
AUTOIGNITION TEMPERATURE:	Not established
DECOMPOSITION TEMPERATURE:	Not established
VISCOSITY:	No data available.
SOLIDS (% by weight):	71.0
VOC, weight percent	Not determined
VOC, U.S. EPA Method 24, less water and exempt solvents (theoretically determined)	357g/liter of material

SAFETY DATA SHEET

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.
CHEMICAL INCOMPATIBILITY: Strong oxidizing agents
HAZARDOUS POLYMERIZATION: Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide Silicon dioxide

SECTION 11: TOXICOLOGICAL INFORMATION

Component Toxicity / Toxicology Data:

COMPONENT NAME	LD50/LC50
Trimethylbenzene, 1,2,4-	Oral LD50 Rat 3,280 mg/kg Inhalation LC50 Rat 18.00 G/M3 Dermal LD50 Rabbit > 3,160.00 MG/KG (NO DEATHS OCCURRED)

This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: No irritation hazard in normal industrial use.

Serious eye damage / irritation :No irritation hazard in normal industrial use.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: No data available.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: No data available.

Specific target organ toxicity-repeated exposure: No data available.

Target organs potentially affected by exposure: Kidneys Central nervous system Lungs Blood

Aspiration hazard: Not an aspiration hazard.

Medical Conditions Aggravated by Exposure: Kidney disease, Lung disease, Blood disorders (like anemia)

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available for this product.
MOBILITY: No data available.
PERSISTENCE: No data available.
BIOACCUMULATION: No data available.

This product has not been tested for ecological effects. Relevant information for components is listed below:

Component:	Ecotoxicity values:
Aromatic petroleum distillate	Acute Toxicity (Fish): LC50 96 h Oncorhynchus mykiss 9.22 mg/L (IUCLID) Acute Toxicity (Daphnia): EC50 48 h Daphnia magna 6.14 mg/L (IUCLID) Acute Toxicity (Algae): Not established
Trimethylbenzene, 1,2,4-	Acute Toxicity (Fish): LC50 96 h Pimephales promelas 7.19 - 8.28 mg/L [flow-through] (EPA) Acute Toxicity (Daphnia): EC50 48 h Daphnia magna 6.14 mg/L (IUCLID) Acute Toxicity (Algae): Not established

SAFETY DATA SHEET

SECTION 13: DISPOSAL CONSIDERATIONS

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

US DOT:	NOT REGULATED
IATA:	NOT REGULATED
IMDG:	NOT REGULATED

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

U.S. EPA TSCA:	This product is in compliance with the Toxic Substances Control Act's Inventory requirements.
CANADIAN CEPA DSL:	The components of this product are included on the DSL or are exempt from DSL requirements.
EUROPEAN REACH:	As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.
AUSTRALIA AICS:	This product is in compliance with the Australian Inventory of Chemical Substances requirements.
JAPAN ENCS:	This product is in compliance with the Japanese Existing and New Chemical Substances requirements.
KOREAN TCCL:	This product is in compliance with the Korean Existing Chemicals List requirements.
PHILIPPINES:	This product is in compliance with the Philippine Inventory of Chemicals and Chemical Substances requirements.
CHINA IECSC INVENTORY:	This product is in compliance with the Inventory of Existing Chemical Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg.request@hbfuller.com to request an export review.

FEDERAL REPORTING

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains crystalline silica. As provided, and during normal use of this product, the crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153.

EPA SARA Title III Section 313

Print Date: 09-27-2018

FOSTER 95-44 CARTRIDGE
802436PM**SAFETY DATA SHEET**

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
1,2,4-Trimethylbenzene	95-63-6	1 - 5
Cumene	98-82-8	0.1 - 1

STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List	CAS	Percent
Quartz (Carcinogen)	14808-60-7	0.1 - 1
Cumene (Carcinogen)	98-82-8	0.1 - 1
Naphthalene (Carcinogen)	91-20-3	0.1 - 1
ethylbenzene (Carcinogen)	100-41-4	0.1 - 1
Methyl isobutyl ketone (Carcinogen)	108-10-1	0.001 - 0.01
Benzene (Carcinogen)	71-43-2	0.001 - 0.01
Methanol (Developmental toxin)	67-56-1	0.001 - 0.01
Methyl isobutyl ketone (Developmental toxin)	108-10-1	0.001 - 0.01
Benzene (Developmental toxin)	71-43-2	0.001 - 0.01
Toluene (Developmental toxin)	108-88-3	< 10 ppm
Benzene, methyl- (Female reproductive toxin)	108-88-3	< 10 ppm
Benzene (Male reproductive toxin)	71-43-2	0.001 - 0.01

Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's at 0.1% or greater, as of the version date of this SDS.

SECTION 16: OTHER INFORMATION

SDS VERSION DATE: 09-26-2018

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 2 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.