

**SAFETY DATA SHEET**

REVISION DATE: 11-02-2016

SUPERSEDES: 08-14-2015

**SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER****PRODUCT INFORMATION**

PRODUCT: CHILDERS CP-76  
PRODUCT DESCRIPTION: Sealant  
INTENDED USE: Sealant  
PRODUCT IDENTIFIER: 801832PM

**COMPANY INFORMATION**

H.B. Fuller Construction Products Inc.  
1105 S. Frontenac Street  
Aurora, IL 60504  
Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758  
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**SECTION 2: HAZARDS IDENTIFICATION****GHS Hazard Symbols:****GHS Signal Word:** Danger**GHS Classification:** Skin Sensitisation Category 1; Carcinogenicity Category 1B; Serious Eye Damage/Eye Irritation Category 2; Reproductive Toxicity Category 2; Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2; Flammable Liquid Category 3; Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3; Hazardous to the aquatic environment - Acute Category 3; Hazardous to the aquatic environment - Chronic Category 3**GHS Hazard Phrases:** Flammable liquid and vapour.; May cause an allergic skin reaction.; Causes serious eye irritation.; May cause respiratory irritation.; May cause drowsiness or dizziness.; May cause cancer.; Suspected of damaging fertility or the unborn child.; May cause damage to organs through prolonged or repeated exposure.; Harmful to aquatic life with long lasting effects.**GHS Precautions:****Safety Precautions:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.**First Aid Measures:** IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several

### SAFETY DATA SHEET

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse. In case of fire: Use water spray, foam, dry chemical or carbon dioxide to extinguish.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	PERCENT	Classification	Note
Feldspar group minerals	68476-25-5	30 - 50	Eye Irrit. 2; H319 STOT SE 3; H335, H336	
Rosin, pentaerythritol ester	8050-26-8	5 - 10		
Polybutene	9003-29-6	1 - 5	Aquatic Chronic 4; H413	
Toluene	108-88-3	1 - 5	Asp. Tox. 1; H304 Acute Tox. 4; H302 Flam. Liq. 2; H225 Repr. 2; H361 Skin Irrit. 2; H315 STOT RE 2; H373 STOT SE 3; H335, H336	
Trimethyl benzene	25551-13-7	1 - 5	Acute Tox. 4; H312 Acute Tox. 4; H302 Eye Irrit. 2; H319 Skin Irrit. 2; H315	
Trimethylbenzene, 1,2,4-	95-63-6	1 - 5	Aquatic Chronic 2; H411 Acute Tox. 4; H332 Acute Tox. 4; H332 Acute Tox. 4; H332 Eye Irrit. 2; H319 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT SE 3; H335, H336	
Tri(nonylphenol)phosphite	26523-78-4	0.1 - 1	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Skin Sens. 1; H317	
Naphthalene	91-20-3	0.1 - 1	Aquatic Chronic 1; H410 Acute Tox. 2; H330 Acute Tox. 4; H302 Carc. 2; H351	

\*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

### SECTION 4: FIRST AID MEASURES

**IF IN EYES:** Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

**IF ON SKIN:** Wash with soap and water. Get medical attention if irritation develops or persists.

**SAFETY DATA SHEET**

IF INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention immediately. Drink two glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person.

**SECTION 5: FIRE FIGHTING MEASURES**

EXTINGUISHING MEDIA: Use water spray, foam, dry chemical or carbon dioxide.  
UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and can travel to a source of ignition and flash back.  
SPECIAL FIRE FIGHTING INSTRUCTIONS: Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.  
HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

SPECIAL PROTECTION: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.  
METHODS FOR CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems.  
Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**SECTION 7: HANDLING AND STORAGE**

Handling: Avoid contacting and avoid breathing the material. Use only in a well ventilated area.  
Keep away from heat, sparks and flame.  
Wash thoroughly after handling.  
Keep container closed.  
Emptied container retains vapor and product residue.  
Observe all labeled precautions until container is cleaned.  
Drums of this material should be grounded when pouring.  
DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.

Storage: Store in a cool, dry, ventilated location. Keep away from heat and flame. Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****EXPOSURE LIMITS:**

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Stoddard solvent	Note P	100 ppm TWA	500 ppm TWA; 2900 mg/m <sup>3</sup> TWA

**SAFETY DATA SHEET**

Toluene		20 ppm TWA	200 ppm TWA 300 ppm Ceiling
Trimethyl benzene		25 ppm TWA	Not established
Calcium carbonate	* (see below)	No data available.	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)
Cumene		50 ppm TWA	50 ppm TWA; 245 mg/m <sup>3</sup> TWA Skin absorption may potentially contribute to the overall exposure to this material.
Naphthalene		10 ppm TWA Skin absorption may potentially contribute to the overall exposure to this material.	10 ppm TWA; 50 mg/m <sup>3</sup> TWA
Ethylbenzene		20 ppm TWA	100 ppm TWA; 435 mg/m <sup>3</sup> TWA

\*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

**ENGINEERING CONTROL METHODS:**

VENTILATION:	General room ventilation might be required under normal conditions of use.
EYE PROTECTION:	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
SKIN PROTECTION:	Avoid skin contact by wearing chemically resistant gloves. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption so that the TLV is not invalidated.
GLOVES:	Nitrile
RESPIRATORY PROTECTION:	No respiratory protection required under normal conditions of use. NIOSH approved air purifying respirator with organic vapor cartridge. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE:	Semi-solid
COLOR:	White
ODOR:	Solvent
ODOR THRESHOLD:	Not established
pH:	Not established
FREEZING/MELTING POINT (deg. C):	Not established
BOILING POINT (deg. C):	Not established
FLASH POINT:	40°C; 104°F Pensky-Martens
EVAPORATION RATE:	Not established
FLAMMABILITY:	Not a flammable solid or gas
UPPER EXPLOSIVE LIMIT (% in air):	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
VAPOR PRESSURE (mm Hg):	Not established

**SAFETY DATA SHEET**

---

VAPOR DENSITY:	Not established
WEIGHT PER GALLON (lbs.):	10.50
SPECIFIC GRAVITY:	1.200
SOLUBILITY:	Not established
OCTANOL/WATER COEFFICIENT:	Not established
AUTOIGNITION TEMPERATURE:	Not established
DECOMPOSITION TEMPERATURE:	Not established
VISCOSITY:	No data available.
SOLIDS (% by weight):	71.7
VOC, weight percent	28.30
VOC, U.S. EPA Method 24, less water and exempt solvents (theoretically determined)	356g/liter of material

**SECTION 10: STABILITY AND REACTIVITY**

---

---

STABILITY:	Stable under normal conditions.
CHEMICAL INCOMPATIBILITY:	Strong oxidizing agents
HAZARDOUS POLYMERIZATION:	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide

**SECTION 11: TOXICOLOGICAL INFORMATION**

---

---

**Component Toxicity / Toxicology Data:**

COMPONENT NAME	LD50/LC50
Toluene	Oral LD50 Rat 636 mg/kg Inhalation LC50 Rat 12.50 mg/l
Trimethyl benzene	Oral LD50 Rat 8,970 mg/kg
Trimethylbenzene, 1,2,4-	Dermal LD50 Rabbit > 3,160.00 mg/kg

**This product is a mixture. Unless noted, the information below is based on components.**

Skin corrosion / irritation: No irritation hazard in normal industrial use.

Serious eye damage / irritation :Can cause moderate irritation, tearing and reddening.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: Contains a substance that is a possible reproductive hazard based on animal studies.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: No data available.

Specific target organ toxicity-repeated exposure: May cause damage to organs through prolonged or repeated exposure.

Target organs potentially affected by exposure: Kidneys Central nervous system Lungs Reproductive system Liver Blood

Aspiration hazard: Not an aspiration hazard.

Medical Conditions Aggravated by Exposure: Kidney disease, Lung disease, Liver disease, Blood disorders (like anemia)

## SAFETY DATA SHEET

### SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW:	No ecological information available for this product.
MOBILITY:	No data available.
PERSISTENCE:	No data available.
BIOACCUMULATION:	No data available.

**This product has not been tested for ecological effects. Relevant information for components is listed below:**

Component:	Ecotoxicity values:
Toluene	<b>Acute Toxicity (Fish):</b> 96 Hr LC50 Pimephales promelas: 15.22 - 19.05 mg/L [flow-through] (1 day old); 96 Hr LC50 Pimephales promelas: 12.6 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 5.89 - 7.81 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 14.1 - 17.16 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 5.8 mg/L [semi-static]; 96 Hr LC50 Lepomis macrochirus: 11.0 - 15.0 mg/L [static]; 96 Hr LC50 Oryzias latipes: 54 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 28.2 mg/L [semi-static]; 96 Hr LC50 Poecilia reticulata: 50.87 - 70.34 mg/L [static] <b>Acute Toxicity (Daphnia):</b> 48 Hr EC50 Daphnia magna: 5.46 - 9.83 mg/L [Static]; 48 Hr EC50 Daphnia magna: 11.5 mg/L <b>Acute Toxicity (Algae):</b> 72 Hr EC50 Pseudokirchneriella subcapitata: 12.5 mg/L [static]
Trimethyl benzene	<b>Acute Toxicity (Fish):</b> 96 Hr LC50 Pimephales promelas: 7.72 mg/L [flow-through] <b>Acute Toxicity (Daphnia):</b> Not established <b>Acute Toxicity (Algae):</b> Not established
Trimethylbenzene, 1,2,4-	<b>Acute Toxicity (Fish):</b> 96 Hr LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-through] <b>Acute Toxicity (Daphnia):</b> 48 Hr EC50 Daphnia magna: 6.14 mg/L <b>Acute Toxicity (Algae):</b> Not established

### SECTION 13: DISPOSAL CONSIDERATIONS

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

LAND DISPOSAL RESTRICTIONS: Toluene Naphthalene ethylbenzene

### SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

US DOT:	NOT REGULATED
IATA:	NOT REGULATED
IMDG:	NOT REGULATED

### SECTION 15: REGULATORY INFORMATION

#### INVENTORY STATUS

U.S. EPA TSCA:	This product is in compliance with the Toxic Substances Control Act's Inventory requirements.
CANADIAN CEPA DSL:	The components of this product are included on the DSL or are exempt from DSL requirements.
EUROPEAN REACH:	As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.
AUSTRALIA AICS:	This product is in compliance with the Australian Inventory of Chemical Substances requirements.
JAPAN ENCS:	This product is in compliance with the Japanese Existing and New

Print Date: 01-09-2017

**SAFETY DATA SHEET**

KOREAN TCCL:	Chemical Substances requirements. This product is in compliance with the Korean Existing Chemicals List requirements.
PHILIPPINES:	This product is in compliance with the Philippine Inventory of Chemicals and Chemical Substances requirements.
CHINA IECSC INVENTORY:	This product is in compliance with the Inventory of Existing Chemical Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at [reg.request@hbfuller.com](mailto:reg.request@hbfuller.com) to request an export review.

This product contains a chemical substance that is subject to a Significant New Use Rule (SNUR) under Section 5(a)(2) of TSCA: 4-Nonylphenol, branched  
79 FR 59186, Oct 1, 2014 (Proposed rule)

**FEDERAL REPORTING**

\*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains crystalline silica. As provided, and during normal use of this product, the crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

## EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
Toluene	108-88-3	1 - 5
1,2,4-Trimethylbenzene	95-63-6	1 - 5
Cumene	98-82-8	0.1 - 1
Naphthalene	91-20-3	0.1 - 1
ethylbenzene	100-41-4	0.1 - 1

## STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List	CAS	Percent
Quartz (Carcinogen)	14808-60-7	1 - 5
Titanium dioxide (Carcinogen)	13463-67-7	0.1 - 1
Cumene (Carcinogen)	98-82-8	0.1 - 1
Naphthalene (Carcinogen)	91-20-3	0.1 - 1
ethylbenzene (Carcinogen)	100-41-4	0.1 - 1
Benzene (Carcinogen)	71-43-2	0.001 - 0.01
Toluene (Developmental toxin)	108-88-3	1 - 5
Benzene (Developmental toxin)	71-43-2	0.001 - 0.01
Benzene, methyl- (Female reproductive toxin)	108-88-3	1 - 5
Benzene (Male reproductive toxin)	71-43-2	0.001 - 0.01

**SAFETY DATA SHEET**

---

**Substances of Very High Concern (SVHC) Content:**

Unless listed below, this product does not contain SVHC's at 0.1% or greater, as of the version date of this SDS.

**SECTION 16: OTHER INFORMATION**

---

---

SDS VERSION DATE: 11-02-2016

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 2 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.