

Print Date: 01-09-2017

FOSTER 65-05
802361PM**SAFETY DATA SHEET**

REVISION DATE: 10-09-2014

SUPERSEDES: 01-10-2012

SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER**PRODUCT INFORMATION**

PRODUCT: FOSTER 65-05
PRODUCT DESCRIPTION: Mastic
INTENDED USE: Adhesive
PRODUCT IDENTIFIER: 802361PM

COMPANY INFORMATION

H.B. Fuller Construction Products Inc.
1105 S. Frontenac Street
Aurora, IL 60504
Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION**GHS Hazard Symbols:****GHS Signal Word:**

Danger

GHS Classification:

Skin Sensitisation Category 1; Reproductive Toxicity Category 1B; Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1; Flammable Liquid Category 3; Hazardous to the aquatic environment - Chronic Category 3

GHS Hazard Phrases:

Flammable liquid and vapour.; May cause an allergic skin reaction.; May damage fertility or the unborn child.; Causes damage to organs through prolonged or repeated exposure.; Harmful to aquatic life with long lasting effects.

GHS Precautions:**Safety Precautions:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.

First Aid Measures:

IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use water spray, foam, dry chemical or carbon dioxide to extinguish.

Storage:

Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked

Print Date: 01-09-2017

FOSTER 65-05
802361PM

SAFETY DATA SHEET

Disposal: up.
Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	PERCENT	Classification	Note
Aliphatic petroleum distillates	64742-88-7	10 - 30	STOT RE 1; H372	
Fuller's earth	8031-18-3	5 - 10	Aquatic Chronic 2; H411 Acute Tox. 4; H302	* (see below)
Crystalline silica	14808-60-7	1 - 5	Carc. 1A; H350 STOT RE 1; H372	* (see below)
Aliphatic amine	28701-67-9	1 - 5	Aquatic Chronic 1; H410 Skin Sens. 1; H317	
Antimony trioxide	1309-64-4	0.1 - 1	Aquatic Acute 1; H400 Carc. 2; H351	* (see below)
Boric acid	10043-35-3	0.1 - 1	Acute Tox. 2; H330 Repr. 1B; H360	

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

IF IN EYES: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:	Use water spray, foam, dry chemical or carbon dioxide.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Vapors are heavier than air and can travel to a source of ignition and flash back.
SPECIAL FIRE FIGHTING INSTRUCTIONS:	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide, Carbon monoxide Sulfur containing gases Chlorine containing gases Nitrogen containing gases

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special

Print Date: 01-09-2017

FOSTER 65-05
802361PM

SAFETY DATA SHEET

circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

METHODS FOR CLEAN-UP: Scrape up and place in disposal container.
Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: Avoid contacting and avoid breathing the material. Use only in a well ventilated area.
Keep away from heat, sparks and flame.
Wash thoroughly after handling.
Keep container closed.
Emptied container retains vapor and product residue.
Observe all labeled precautions until container is cleaned.
Drums of this material should be grounded when pouring.
DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.

Storage: Store in a cool, dry, ventilated location. Keep away from heat and flame. Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS:

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Asphalt (petroleum)		0.5 mg/m ³ TWA (fume, inhalable fraction, as benzene soluble aerosol)	Not established
Crystalline silica	* (see below)	0.025 mg/m ³ TWA (respirable fraction)	((250)/(%SiO ₂ + 5) mppcf TWA (respirable)); ((10)/(%SiO ₂ + 2) mg/m ³ TWA (respirable)); ((30)/(%SiO ₂ + 2) mg/m ³ TWA (total dust))
Cellulose	* (see below)	10 mg/m ³ TWA	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)
Boric acid		2 mg/m ³ TWA (inhalable fraction, listed under Borate compounds, inorganic) 6 mg/m ³ STEL (inhalable fraction, listed under Borate compounds, inorganic)	Not established

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

ENGINEERING CONTROL METHODS:

VENTILATION: Use local exhaust ventilation or other engineering controls to minimize exposures.

EYE PROTECTION: Wear safety glasses with side shields when handling this product.
Wear additional eye protection such as chemical splash goggles

Print Date: 01-09-2017

FOSTER 65-05
802361PM**SAFETY DATA SHEET**

	and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
SKIN PROTECTION:	Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt. An apron may be appropriate if splashing can occur.
GLOVES:	Nitrile
RESPIRATORY PROTECTION:	Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Semi-solid
COLOR:	Black
ODOR:	Solvent
ODOR THRESHOLD:	Not established
pH:	Not established
FREEZING/MELTING POINT (deg. C):	Not established
BOILING POINT (deg. C):	Not established
FLASH POINT:	40°C; 104°F TCC
EVAPORATION RATE:	Not established
FLAMMABILITY:	Not a flammable solid or gas
UPPER EXPLOSIVE LIMIT (% in air):	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
VAPOR PRESSURE (mm Hg):	Not established
VAPOR DENSITY:	Not established
WEIGHT PER GALLON (lbs.):	9.70
SPECIFIC GRAVITY:	1.170
SOLUBILITY:	Not established
OCTANOL/WATER COEFFICIENT:	Not established
AUTOIGNITION TEMPERATURE:	Not established
DECOMPOSITION TEMPERATURE:	Not established
VISCOSITY:	No data available.
SOLIDS (% by weight):	79.0
VOC, weight percent	20.33
VOC, U.S. EPA Method 24, less water and exempt solvents (theoretically determined)	238g/liter of material

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Stable under normal conditions.
CHEMICAL INCOMPATIBILITY:	Not established
HAZARDOUS POLYMERIZATION:	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS:	Sulfur containing gases Carbon monoxide, carbon dioxide Chlorine containing gases Nitrogen containing gases

SECTION 11: TOXICOLOGICAL INFORMATION

Print Date: 01-09-2017

FOSTER 65-05
802361PM

SAFETY DATA SHEET

Component Toxicity / Toxicology Data:

COMPONENT NAME	LD50/LC50
Asphalt (petroleum)	ORAL LD50 RAT > 5,000 MG/KG DERMAL LD50 RABBIT > 2,000.00 MG/KG
Aliphatic petroleum distillates	ORAL LD50 RAT > 5,000 MG/KG INHALATION LC50-4H RAT > 5 MG/L DERMAL LD50 RABBIT 3,000.00 MG/KG
Crystalline silica	ORAL LD50 RAT 500 MG/KG
Cellulose	INHALATION LC50-4H RAT > 5,800 MG/M3

This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Serious eye damage / irritation :Can cause moderate irritation, tearing and reddening.

Respiratory / skin sensitization: May cause an allergic skin reaction.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: Contains a substance that is a possible reproductive hazard based on animal studies.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: No data available.

Specific target organ toxicity-single exposure: Causes damage to organs through prolonged or repeated exposure.

Target organs potentially affected by exposure: Skin Lungs Central nervous system Reproductive system

Aspiration hazard: No data available.

Medical Conditions Aggravated by Exposure: Skin disease including eczema and sensitization, Lung disease

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available for this product.
 MOBILITY: No data available.
 PERSISTENCE: No data available.
 BIOACCUMULATION: No data available.

This product has not been tested for ecological effects. Relevant information for components is listed below:

Component:	Ecotoxicity values:
Aliphatic petroleum distillates	Acute Toxicity (Fish): 96 Hr LC50 Pimephales promelas: 800 mg/L [static] Acute Toxicity (Daphnia): 48 Hr EC50 Daphnia magna: >100 mg/L Acute Toxicity (Algae): 96 Hr EC50 Pseudokirchneriella subcapitata: 450 mg/L
Chlorinated paraffin	Acute Toxicity (Fish): 96 Hr LC50 Lepomis macrochirus: >300 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: >0.0109 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 94.5 - 271 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >0.1 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: >100 mg/L [static] Acute Toxicity (Daphnia): Not established Acute Toxicity (Algae): Not established

SECTION 13: DISPOSAL CONSIDERATIONS

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

Print Date: 01-09-2017

FOSTER 65-05
802361PM**SAFETY DATA SHEET****SECTION 14: TRANSPORT INFORMATION**

Consult Bill of Lading for transportation information.

US DOT: NOT REGULATED
IATA: NOT REGULATED**SECTION 15: REGULATORY INFORMATION****INVENTORY STATUS**

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt from DSL requirements.

EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.

AUSTRALIA AICS: This product is in compliance with the Australian Inventory of Chemical Substances requirements.

KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List requirements.

PHILIPPINES: This product is in compliance with the Philippine Inventory of Chemicals and Chemical Substances requirements.

CHINA IECSC INVENTORY: This product is in compliance with the Inventory of Existing Chemical Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg.request@hbfuller.com to request an export review.

FEDERAL REPORTING**EPA SARA Title III Section 313**

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
Antimony compounds	1309-64-4	0.1 - 1

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

B3
D2A D2B**STATE REPORTING**

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List	CAS	Percent
Quartz (Carcinogen)	14808-60-7	1 - 5
Antimony(III) oxide (Carcinogen)	1309-64-4	0.1 - 1
ISOBUTYL METHYL KETONE (Carcinogen)	108-10-1	0.001 - 0.01
Lead (Carcinogen)	7439-92-1	< 10 ppm

Print Date: 01-09-2017

FOSTER 65-05
802361PM**SAFETY DATA SHEET**

Arsenic compounds (inorganic)	(Carcinogen)	7440-38-2	< 10 ppm
Methanol	(Developmental toxin)	67-56-1	0.01 - 0.1
Methyl isobutyl ketone	(Developmental toxin)	108-10-1	0.001 - 0.01
Lead	(Developmental toxin)	7439-92-1	< 10 ppm
Lead	(Female reproductive toxin)	7439-92-1	< 10 ppm
Lead	(Male reproductive toxin)	7439-92-1	< 10 ppm

Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's.

Boric acid

SECTION 16: OTHER INFORMATION

SDS VERSION DATE: 10-09-2014

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 2 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B.Fuller Construction Products, Inc. from its suppliers, and because H.B.Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B.Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B.Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B.Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.