

Childers™ CHIL-LASTIC™ CP-79T

Version 1.0 Revision Date 11/12/2021

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Childers™ CHIL-LASTIC™ CP-79T

Product code : 100000015399

Manufacturer or supplier's details

Company : H.B. Fuller Company

Address : 1200 Willow Lake Boulevard

Vadnais Heights, MN 55110

Telephone : 1-888-423-8553

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Solvent based adhesive

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Pasty solid
Color	black
Odor	solvent

GHS Classification

Flammable liquids : Category 3
Skin irritation : Category 2
Eye irritation : Category 2A
Germ cell mutagenicity : Category 1B
Carcinogenicity : Category 1A

GHS label elements

Hazard pictograms







Signal Word : Danger



Childers™ CHIL-LASTIC™ CP-79T

Version 1.0

Revision Date 11/12/2021

Hazard Statements:

H226 Flammable liquid and vapor. H315 Causes skin irritation. H319 Causes serious eye irritation. H340 May cause genetic defects. H350 May cause cancer.

Precautionary Statements:

Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P264 Wash skin thoroughly after handling. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. **Disposal:** P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Carcinogenicity:

Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

benzene 71-43-2

Group 2A: Probably carcinogenic to humans Asphalt, oxidized 64742-93-4

Group 2B: Possibly carcinogenic to humans Naphtha (petroleum), 64742-48-9

hydrotreated heavy

OSHA Specifically regulated carcinogen

benzene 71-43-2

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7

benzene 71-43-2



Childers™ CHIL-LASTIC™ CP-79T

Version 1.0 Revision Date 11/12/2021

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
Asphalt, oxidized	64742-93-4	20 - 30
3-(isodecyloxy)propylammonium acetate	28701-67-9	20 - 30
Naphtha (petroleum), hydrotreated heavy	64742-48-9	10 - 20
Quartz (SiO2)	14808-60-7	1 - 5
benzene	71-43-2	0.1 - 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Show this material safety data sheet to the doctor in

attendance.

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.

Get medical attention if irritation develops and persists.

In case of eye contact : Flush eyes with water at least 15 minutes. Get medical

attention if eye irritation develops or persists.

If swallowed : Do NOT induce vomiting.

If victim is fully conscious, give a cupful of water.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Specific hazards during fire

fighting

: Cool closed containers exposed to fire with water spray.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.



Childers™ CHIL-LASTIC™ CP-79T

Version 1.0 Revision Date 11/12/2021

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.

Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

: Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material.

Sweep up and shovel into suitable containers for disposal.

Non-sparking tools should be used.

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid inhalation of vapor or mist.

Do not use in areas without adequate ventilation. Keep away from fire, sparks and heated surfaces.

Keep container closed when not in use.

Take precautionary measures against static discharges.

Conditions for safe storage : Take

Take measures to prevent the build up of electrostatic charge.

Use explosion-proof equipment.

Keep containers tightly closed in a dry, cool and well-

ventilated place.

Keep away from sources of ignition - No smoking.

Solvent vapors are heavier than air and may spread along

floors.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum),	64742-48-9	TWA	500 ppm	OSHA Z-1



Childers™ CHIL-LASTIC™ CP-79T

Version 1.0

Revision Date 11/12/2021

hydrotreated heavy			2,000 mg/m3	
		TWA	400 ppm 1,600 mg/m3	OSHA P0
Quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
benzene	71-43-2	TWA	0.5 ppm	ACGIH
		STEL	2.5 ppm	ACGIH
		TWA	0.1 ppm	NIOSH REL
		ST	1 ppm	NIOSH REL
		TWA	10 ppm	OSHA Z-2
		CEIL	25 ppm	OSHA Z-2
		Peak	50 ppm	OSHA Z-2
		PEL	1 ppm	OSHA CARC
		STEL	5 ppm	OSHA CARC
		PEL	1 ppm	CAL PEL
		STEL	5 ppm	CAL PEL

Engineering measures : Use local exhaust ventilation or other engineering controls to

minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapor Type



Childers™ CHIL-LASTIC™ CP-79T

Version 1.0 Revision Date 11/12/2021

Hand protection

Material : Nitrile rubber

Eye protection : Safety glasses with side-shields

Hygiene measures : Avoid contact with skin, eyes and clothing.

Provide adequate ventilation.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Pasty solid Color : black Odor : solvent

Odor Threshold : No data available pH : Not applicable Melting point/freezing point : is not determined Boiling point/boiling range : is not determined

Flash point : 37.8 °CMethod: Cleveland open cup

Evaporation rate : is not determined Upper explosion limit : Upper flammability limit

is not determined

Lower explosion limit : Lower flammability limit

is not determined

Vapor pressure : is not determined

Density : 8.4 - 8.8 lb/gal

Solubility(ies)

Water solubility : is not determined Partition coefficient: n- : No data available

octanol/water

Autoignition temperature : is not determined

Viscosity

Viscosity, kinematic : is not determined

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Hazardous polymerization does not occur.



Childers™ CHIL-LASTIC™ CP-79T

Version 1.0 Revision Date 11/12/2021

Conditions to avoid : Heat, flames and sparks.

Hazardous decomposition

products

: Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 2,008 mg/kg

Method: Calculation method

Components:

benzene:

Acute inhalation toxicity : LC50 Rat: 13050 ppm

Exposure time: 4 h
Test atmosphere: vapor

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity



Childers™ CHIL-LASTIC™ CP-79T

Version 1.0 Revision Date 11/12/2021

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Asphalt, oxidized:

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (microalgae)): 56 mg/l

Exposure time: 72 h

Test Type: flow-through test

Naphtha (petroleum), hydrotreated heavy:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,200 mg/l

Exposure time: 96 h Test Method: static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia): 2.6 mg/l Exposure time: 96 h

Test Method: static test

benzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.3 mg/l

Exposure time: 96 h

Test Method: flow-through test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 8.76 - 15.6 mg/l

Exposure time: 48 h Test Method: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (microalgae)): 29 mg/l

Exposure time: 72 h

Test Type: flow-through test

Persistence and degradability

No data available

Bioaccumulative potential

Mobility in soil

No data available

Other adverse effects

No data available



Childers™ CHIL-LASTIC™ CP-79T

Version 1.0

Revision Date 11/12/2021

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Germ cell mutagenicity

Carcinogenicity

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302

EHS TPO.



Childers™ CHIL-LASTIC™ CP-79T

Version 1.0 Revision Date 11/12/2021

SARA 313 : The following components are subject to reporting levels established

by SARA Title III, Section 313:

benzene 71-43-2

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR

61):

benzene 71-43-2

US State Regulations

California Prop 65 Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

TCSI On the inventory, or in compliance with the inventory **TSCA** All substances listed as active on the TSCA inventory AIIC On the inventory, or in compliance with the inventory DSL All components of this product are on the Canadian DSL **ENCS** On the inventory, or in compliance with the inventory **KECI** On the inventory, or in compliance with the inventory **PICCS** On the inventory, or in compliance with the inventory **IECSC** On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory **NZIoC**

Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com




Childers™ CHIL-LASTIC™ CP-79T

Version 1.0

Revision Date 11/12/2021

Further information



HMIS III:

HEALTH	2*
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.