

Childers[™] CHIL-PRUF[™] CP-24

Version 1.0

Revision Date 02/28/2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	Childers™ CHIL-PRUF™ CP-24
Product code	:	10000015404

Manufacturer or supplier's details

Company	:	H.B. Fuller Company
Address	:	1200 Willow Lake Boulevard Vadnais Heights, MN 55110
Telephone	:	1-888-423-8553

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use	:	Solvent based adhesive
Restrictions on use	:	For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	paste
Color	black
Odor	solvent

GHS Classification

Flammable liquids Skin sensitization Germ cell mutagenicity Carcinogenicity Aspiration hazard	 Category 3 Category 1 Category 1B Category 1A Category 1
GHS label elements	
Hazard pictograms	
Signal Word	: Danger

Hazard Statements:

H226 Flammable liquid and vapor. H304 May be fatal if swallowed and enters airways. H317 May



Childers[™] CHIL-PRUF[™] CP-24

Version 1.0

Revision Date 02/28/2024

cause an allergic skin reaction. H340 May cause genetic defects. H350 May cause cancer. **Precautionary Statements:**

Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing mist or vapors. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. **Response:** P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P331 Do NOT induce vomiting. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P363 Wash contaminated clothing before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. **Disposal:** P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Carcinogenicity:

IARC	Group 1: Carcinogenic to humans benzene	5 71-43-2
	Quartz (SiO2)	14808-60-7
	Group 2A: Probably carcinogenic	to humans
	Asphalt, oxidized	64742-93-4
	Group 2B: Possibly carcinogenic	to humans
	Naphtha (petroleum), hydrotreated heavy	64742-48-9
OSHA	OSHA specifically regulated carc benzene	vinogen 71-43-2
NTP	Known to be human carcinogen	
	benzene	71-43-2
	Quartz (SiO2)	14808-60-7

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name CAS	S-No. Concentration [%]	
-------------------	-------------------------	--



Childers[™] CHIL-PRUF[™] CP-24

Version 1.0

Revision Date 02/28/2024

Asphalt, oxidized	64742-93-4	50 - 70
Naphtha (petroleum), hydrotreated heavy	64742-48-9	30 - 50
benzene	71-43-2	0.1 - 1
Quartz (SiO2)	14808-60-7	0.1 - 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	: Show this material safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. If symptoms persist, call a physician.
In case of skin contact	: Wash off with soap and water. Get medical attention if irritation develops and persists.
In case of eye contact	: Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
If swallowed	 Do NOT induce vomiting. If victim is fully conscious, give a cupful of water. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	 May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May cause genetic defects. May cause cancer.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Specific hazards during fire fighting	: Cool closed containers exposed to fire with water spray.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, :	Remove all sources of ignition.
protective equipment and	Beware of vapors accumulating to form explosive
emergency procedures	concentrations. Vapors can accumulate in low areas.
	Refer to protective measures listed in sections 7 and 8.



Childers™ CHIL-PRUF™ CP-24	
Version 1.0	Revision Date 02/28/2024
Environmental precautions	: Prevent spreading over a wide area (e.g., by containment or oil barriers).
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Non-sparking tools should be used.
SECTION 7. HANDLING AND STO	DRAGE
Local/Total ventilation	: Use only with adequate ventilation.
Advice on safe handling	 Avoid inhalation of vapor or mist. Do not use in areas without adequate ventilation. Keep away from fire, sparks and heated surfaces. Keep container closed when not in use. Take precautionary measures against static discharges.
Conditions for safe storage	 Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Keep containers tightly closed in a dry, cool and well- ventilated place. Keep away from sources of ignition - No smoking. Solvent vapors are heavier than air and may spread along floors.
Materials to avoid	: Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum), hydrotreated heavy	64742-48-9	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
benzene	71-43-2	TWA	0.5 ppm	ACGIH
		STEL	2.5 ppm	ACGIH
		TWA	0.1 ppm	NIOSH REL
		ST	1 ppm	NIOSH REL
		TWA	10 ppm	OSHA Z-2
		CEIL	25 ppm	OSHA Z-2
		Peak	50 ppm	OSHA Z-2



Childers[™] CHIL-PRUF[™] CP-24

Version 1.0

Revision Date 02/28/2024

		PEL	1 ppm	OSHA CARC
		STEL	5 ppm	OSHA CARC
		PEL	1 ppm	CAL PEL
		STEL	5 ppm	CAL PEL
Quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL
		TWÁ (respirable dust fraction)	0.1 mg/m3	OSHA P0

Engineering measures	:	Use local exhaust ventilation or other engineering controls to minimize exposures.
Personal protective equipme	ent	
Respiratory protection	:	Use respiratory protection unless adequate risk management measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	:	Organic vapor Type
Hand protection Material	:	Nitrile rubber
Eye protection	:	Safety glasses with side-shields
Hygiene measures	:	Avoid contact with skin, eyes and clothing. Provide adequate ventilation.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES



Childers[™] CHIL-PRUF[™] CP-24

Version 1.0

Revision Date 02/28/2024

Appearance	: paste
Color	: black
Odor	: solvent
Odor Threshold	: no data available
рН	: Not applicable
Melting point/freezing point	: is not determined
Boiling point/boiling range	: is not determined
Flash point	: 39 °CMethod: Cleveland open cup
Evaporation rate	: is not determined
Upper explosion limit	: Upper flammability limit is not determined
Lower explosion limit	: Lower flammability limit
	is not determined
Vapor pressure	: is not determined
Density	: 8.5 lb/gal
Solubility(ies)	: is not determined
Water solubility	. Is not determined
Partition coefficient: n- octanol/water	: no data available
Autoignition temperature	: is not determined
Viscosity	
Viscosity, kinematic	: is not determined
VOC, less water, in g/l	: 350

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Hazardous polymerization does not occur.
Conditions to avoid	: Heat, flames and sparks.
Hazardous decomposition products	: Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Components:

- benzene:
- Acute inhalation toxicity : LC50 Rat: 13050 ppm



Childers[™] CHIL-PRUF[™] CP-24

Version 1.0

Revision Date 02/28/2024

Exposure time: 4 h Test atmosphere: vapor

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

Product:

Classification: May cause sensitization by skin contact.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

<u>Components:</u> Asphalt, oxidized :	
Toxicity to algae	 EC50 (Pseudokirchneriella subcapitata (microalgae)): 56 mg/l Exposure time: 72 h Test Type: flow-through test
Naphtha (petroleum), hydrot	reated heavy :
Toxicity to fish	 LC50 (Pimephales promelas (fathead minnow)): 2,200 mg/l Exposure time: 96 h Test Method: static test



Childers[™] CHIL-PRUF[™] CP-24

Version 1.0	Revision Date 02/28/2024
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia): 2.6 mg/l Exposure time: 96 h Test Method: static test
benzene :	
Toxicity to fish	 LC50 (Oncorhynchus mykiss (rainbow trout)): 5.3 mg/l Exposure time: 96 h Test Method: flow-through test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 8.76 - 15.6 mg/l Exposure time: 48 h Test Method: static test
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (microalgae)): 29 mg/l Exposure time: 72 h Test Type: flow-through test
Persistence and degradability	
No data available Bioaccumulative potential	
Components: benzene : Partition coefficient: n- octanol/water	: log Pow: 1.56 - 2.15 (25 °C) GLP: no
Mobility in soil	
No data available	
Other adverse effects	
No data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements. The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION

International Regulations



Childers[™] CHIL-PRUF[™] CP-24

Version 1.0

Revision Date 02/28/2024

IATA-DGR		
UN/ID No.	:	UN 1999
Proper shipping name	:	Tars, liquid
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355
IMDG-Code		
UN number		UN 1999
Proper shipping name	:	TARS, LIQUID
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, S-E
Marine pollutant	:	no
Remarks	:	Transport in accordance with 2.3.2.5 of the IMDG Code: in quantities less than 30 L, not regulated as a hazardous material.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR UN/ID/NA number Proper shipping name	: UN 1999 : Tars, liquid
Class	: 3
Packing group	: III
Labels	: FLAMMABLE LIQUID
ERG Code	: 130
Marine pollutant	: no
Remarks	: PACKAGES <450 L NOT REGULATED, CFR 173.150(f)(2)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards	: Flammable (gases, aerosols, liquids, or solids) Germ cell mutagenicity Carcinogenicity
	9 / 11




Childers™ CHIL-PRUF™ CP-24		
Version 1.0	Revision Date 02/28/2024	
	Aspiration hazard Respiratory or skin sensitization	
SARA 302	: This material does not contain any components with a section 302 EHS TPQ.	
SARA 313	: The following components are subject to reporting levels established by SARA Title III, Section 313:	
	benzene 71-43-2	
Clean Air Act		
The following chemical(s) 61):) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR	
benzene	71-43-2	
US State Regulations		
California Prop 65	Please contact Supplier for more information.	
The ingredients of this TSCA	product are reported in the following inventories: All substances listed as active on the TSCA inventory	
DSL	All components of this product are on the Canadian DSL	
AIIC	On the inventory, or in compliance with the inventory	
NZIoC	On the inventory, or in compliance with the inventory	
ENCS	On the inventory, or in compliance with the inventory	
KECI	On the inventory, or in compliance with the inventory	
PICCS	On the inventory, or in compliance with the inventory	
IECSC	On the inventory, or in compliance with the inventory	
	On the inventory, or in compliance with the inventory CA (USA), DSL (Canada), REACH(Europe), AIIC (Australia), NZIoC (New , KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)	

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com





The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.