

Childers™ CHIL-JOINT® CP-70-C

Version 1.0 Revision Date 12/21/2020

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Childers™ CHIL-JOINT® CP-70-C

Product code : 100000013788

Manufacturer or supplier's details

Company : H.B. Fuller Construction Products

Address : 1105 South Frontenac

Aurora, IL, 60504

Telephone : 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Solvent based sealant

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Color	gray
Odor	solvent

GHS Classification

Skin sensitization : Category 1
Germ cell mutagenicity : Category 1B

GHS label elements

Hazard pictograms



Signal Word : Danger

Hazard Statements:

H317 May cause an allergic skin reaction. H340 May cause genetic defects.

Precautionary Statements:

Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety



Childers™ CHIL-JOINT® CP-70-C

Version 1.0

Revision Date 12/21/2020

precautions have been read and understood. P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P363 Wash contaminated clothing before reuse.

Storage: P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Carcinogenicity:

IARC Group 1: Carcinogenic to humans During normal handling of the

product, this substance is encapsulated within the product and

will not present a cancer exposure risk.

Quartz (SiO2) 14808-60-7

OSHANo component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogenDuring normal handling of the

product, this substance is encapsulated within the product and

will not present a cancer exposure risk.

Quartz (SiO2) 14808-60-7

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
calcium carbonate	471-34-1	50 - 70
Stoddard solvent	8052-41-3	1 - 5
Quartz (SiO2)	14808-60-7	0.1 - 1
cobalt bis(2-ethylhexanoate)	136-52-7	0.1 - 1
Solvent naphtha (petroleum), light arom.	64742-95-6	0.1 - 1
butanone oxime	96-29-7	0.1 - 1
Distillates (petroleum), hydrotreated light	64742-47-8	0.1 - 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Show this material safety data sheet to the doctor in

attendance.



Childers™ CHIL-JOINT® CP-70-C

Version 1.0 Revision Date 12/21/2020

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.

Get medical attention if irritation develops and persists.

In case of eye contact : Flush eyes with water at least 15 minutes. Get medical

attention if eye irritation develops or persists.

If swallowed : Do NOT induce vomiting.

If victim is fully conscious, give a cupful of water.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Specific hazards during fire

fighting

: Cool closed containers exposed to fire with water spray.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.

Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material.

Sweep up and shovel into suitable containers for disposal.

Non-sparking tools should be used.

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid inhalation of vapor or mist.



Childers™ CHIL-JOINT® CP-70-C

Version 1.0 Revision Date 12/21/2020

Do not use in areas without adequate ventilation. Keep away from fire, sparks and heated surfaces.

Keep container closed when not in use.

Take precautionary measures against static discharges.

Conditions for safe storage : Take measures to prevent the build up of electrostatic charge.

Use explosion-proof equipment.

Keep containers tightly closed in a dry, cool and well-

ventilated place.

Keep away from sources of ignition - No smoking.

Solvent vapors are heavier than air and may spread along

floors.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
calcium carbonate	471-34-1	PEL (Total dust)	10 mg/m3	CAL PEL
		PEL (respirable dust fraction)	5 mg/m3	CAL PEL
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		С	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
Quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m3	OSHA P0



Childers™ CHIL-JOINT® CP-70-C

Version 1.0 Revision Date 12/21/2020

		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	200 mg/m3	ACGIH
		TWA	400 ppm 1,600 mg/m3	OSHA P0
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	200 mg/m3	ACGIH
		TWA	400 ppm 1,600 mg/m3	OSHA P0

Engineering measures : Use local exhaust ventilation or other engineering controls to

minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapor Type

Hand protection

Material : Nitrile rubber

Eye protection : Safety glasses with side-shields

Hygiene measures : Avoid contact with skin, eyes and clothing.

Provide adequate ventilation.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Color : gray
Odor : solvent

Odor Threshold : No data available Melting point/freezing point : is not determined



Childers™ CHIL-JOINT® CP-70-C

Version 1.0 Revision Date 12/21/2020

Boiling point/boiling range : is not determined

Evaporation rate : is not determined Upper explosion limit : Upper flammability limit

is not determined

Lower explosion limit : Lower flammability limit

is not determined

Density : 13.2 - 14.2 lb/gal

Solubility(ies)

Water solubility : is not determined
Partition coefficient: n- : No data available

octanol/water

Autoignition temperature : is not determined

Viscosity

Viscosity, kinematic : is not determined

VOC, less water, in g/l : 66

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Hazardous polymerization does not occur.

Conditions to avoid : Heat, flames and sparks.

Hazardous decomposition

products

: Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:

Solvent naphtha (petroleum), light arom.:

Acute inhalation toxicity : LC50 Rat: > 5.2 mg/l

Exposure time: 4 h



Childers™ CHIL-JOINT® CP-70-C

Version 1.0 Revision Date 12/21/2020

Acute dermal toxicity : LD50 Dermal Rabbit: > 2,000 mg/kg

butanone oxime:

Acute oral toxicity : LD50 Oral Rat: 930 mg/kg

Distillates (petroleum), hydrotreated light:

Acute inhalation toxicity : LC50 Rat: > 5.2 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Solvent naphtha (petroleum), light arom. :

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 9.22 mg/l

Exposure time: 96 h



Childers™ CHIL-JOINT® CP-70-C

Version 1.0 Revision Date 12/21/2020

Test Method: static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 6.14 mg/l

Exposure time: 48 h Test Method: static test

butanone oxime:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 320 - 1,000 mg/l

Exposure time: 96 h
Test Method: static test

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 83 mg/l

Exposure time: 72 h

Test Type: flow-through test

Distillates (petroleum), hydrotreated light:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 2.2 mg/l

Exposure time: 96 h
Test Method: static test

Persistence and degradability

No data available

Bioaccumulative potential

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : This product meets the definition of hazardous waste under

the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial

authorities for more restrictive requirements.

The hazard and precautionary statements displayed on the

label also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION

Special precautions for user



Childers™ CHIL-JOINT® CP-70-C

Version 1.0

Revision Date 12/21/2020

Not applicable

Domestic regulation

49 CFR

Not regulated as a dangerous good

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Respiratory or skin sensitization

Germ cell mutagenicity

SARA 302 : This material does not contain any components with a section 302

EHS TPQ.

SARA 313 : This material does not contain any chemical components with known

CAS numbers that exceed the threshold (De Minimis) reporting levels

established by SARA Title III, Section 313.

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

cobalt bis(2-ethylhexanoate) 136-52-7

US State Regulations

California Prop 65 Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

TSCA All substances listed as active on the TSCA inventory



Childers™ CHIL-JOINT® CP-70-C

Version 1.0

Revision Date 12/21/2020

AICS
On the inventory, or in compliance with the inventory
ENCS
On the inventory, or in compliance with the inventory
KECI
On the inventory, or in compliance with the inventory
On the inventory, or in compliance with the inventory
PICCS
On the inventory, or in compliance with the inventory
On the inventory, or in compliance with the inventory
INVENTOR ON THE INVEN


(Taiwan)

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Department - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

Further information





HMIS III:

HEALTH	2*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.