

Childers™ CHIL-BYL® CP-76

Version 1.0 Revision Date 12/22/2020

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Childers™ CHIL-BYL® CP-76

Product code : 100000015211

Manufacturer or supplier's details

Company : H.B. Fuller Construction Products

Address : 1105 South Frontenac

Aurora, IL, 60504

Telephone : 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Solvent based sealant

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	viscous liquid
Color	white
Odor	solvent

GHS Classification

Eye irritation : Category 2A
Skin sensitization : Category 1
Germ cell mutagenicity : Category 1B
Reproductive toxicity : Category 2

Specific target organ toxicity -

single exposure

: Category 3 (Respiratory system)

Specific target organ toxicity - : Category 2

repeated exposure

Aspiration hazard : Category 1

GHS label elements



Childers™ CHIL-BYL® CP-76

Version 1.0 Revision Date 12/22/2020

Hazard pictograms :





Signal Word : Danger

Hazard Statements:

H304 May be fatal if swallowed and enters airways. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H340 May cause genetic defects. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements:

Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P331 Do NOT induce vomiting. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P363 Wash contaminated clothing before reuse.

Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Carcinogenicity:

IARC Group 1: Carcinogenic to humansDuring normal handling of the

product, this substance is encapsulated within the product and

will not present a cancer exposure risk.

Quartz (SiO2) 14808-60-7

Group 2B: Possibly carcinogenic to humansDuring normal handling of the product, this substance is encapsulated within the product

and will not present a cancer exposure risk.

titanium dioxide 13463-67-7

cumene 98-82-8

ethylbenzene 100-41-4

naphthalene 91-20-3



NTP

Childers™ CHIL-BYL® CP-76

Version 1.0 Revision Date 12/22/2020

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

Known to be human carcinogenDuring normal handling of the

product, this substance is encapsulated within the product and

will not present a cancer exposure risk.

Quartz (SiO2) 14808-60-7

Reasonably anticipated to be a human carcinogenDuring normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.

cumene 98-82-8

naphthalene 91-20-3

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
Feldspar-group minerals	68476-25-5	30 - 50
Stoddard solvent	8052-41-3	20 - 30
Quartz (SiO2)	14808-60-7	1 - 5
calcium carbonate	471-34-1	1 - 5
toluene	108-88-3	1 - 5
trimethylbenzene	25551-13-7	1 - 5
Solvent naphtha (petroleum), light arom.	64742-95-6	1 - 5
1,2,4-trimethylbenzene	95-63-6	1 - 5
titanium dioxide	13463-67-7	0.1 - 1
tris(nonylphenyl) phosphite	26523-78-4	0.1 - 1
cumene	98-82-8	0.1 - 1
ethylbenzene	100-41-4	0.1 - 1
naphthalene	91-20-3	0.1 - 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Show this material safety data sheet to the doctor in

attendance.

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.



Childers™ CHIL-BYL® CP-76

Version 1.0 Revision Date 12/22/2020

Get medical attention if irritation develops and persists.

In case of eye contact : Flush eyes with water at least 15 minutes. Get medical

attention if eye irritation develops or persists.

If swallowed : Do NOT induce vomiting.

If victim is fully conscious, give a cupful of water.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Specific hazards during fire

fighting

: Cool closed containers exposed to fire with water spray.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.

Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material.

Sweep up and shovel into suitable containers for disposal.

Non-sparking tools should be used.

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid inhalation of vapor or mist.

Do not use in areas without adequate ventilation. Keep away from fire, sparks and heated surfaces.

Keep container closed when not in use.

Take precautionary measures against static discharges.



Childers™ CHIL-BYL® CP-76

Version 1.0 Revision Date 12/22/2020

Conditions for safe storage : Take measures to prevent the build up of electrostatic charge.

Use explosion-proof equipment.

Keep containers tightly closed in a dry, cool and well-

ventilated place.

Keep away from sources of ignition - No smoking.

Solvent vapors are heavier than air and may spread along

floors.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		С	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
Quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0



Childers™ CHIL-BYL® CP-76

Version 1.0

Revision Date 12/22/2020

calcium carbonate	471-34-1	PEL (Total dust)	10 mg/m3	CAL PEL
		PEL (respirable dust fraction)	5 mg/m3	CAL PEL
toluene	108-88-3	TWA	20 ppm	ACGIH
tolderic	100 00 0	TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		TWA	100 ppm	OSHA P0
			375 mg/m3	
		STEL	150 ppm	OSHA P0
			560 mg/m3	
		PEL	10 ppm	CAL PEL
			37 mg/m3	
		С	500 ppm	CAL PEL
		STEL	150 ppm 560 mg/m3	CAL PEL
trimethylbenzene	25551-13-7	TWA	25 ppm	ACGIH
		TWA	25 ppm	OSHA P0
			125 mg/m3	
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	200 mg/m3	ACGIH
		TWA	400 ppm 1,600 mg/m3	OSHA P0
titanium dioxide	13463-67-7	TWA	10 mg/m3	ACGIH
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total)	10 mg/m3	OSHA P0
		TWA (Total dust)	10 mg/m3	OSHA P0
cumene	98-82-8	TWA	50 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0
		PEL	50 ppm 245 mg/m3	CAL PEL
ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		STEL	125 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0



Childers™ CHIL-BYL® CP-76

Version 1.0 Revision Date 12/22/2020

		PEL	5 ppm 22 mg/m3	CAL PEL
		STEL	30 ppm 130 mg/m3	CAL PEL
naphthalene	91-20-3	TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		TWA	10 ppm 50 mg/m3	NIOSH REL
		ST	15 ppm 75 mg/m3	NIOSH REL
		TWA	10 ppm 50 mg/m3	OSHA Z-1
		TWA	10 ppm 50 mg/m3	OSHA P0
		STEL	15 ppm 75 mg/m3	OSHA P0
		PEL	0.1 ppm 0.5 mg/m3	CAL PEL

Engineering measures : Use local exhaust ventilation or other engineering controls to

minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapor Type

Hand protection

Material : Nitrile rubber

Eye protection : Safety glasses with side-shields

Hygiene measures : Avoid contact with skin, eyes and clothing.

Provide adequate ventilation.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid
Color : white
Odor : solvent

Odor Threshold : No data available

Melting point/freezing point : is not determined

Boiling point/boiling range : is not determined



Childers™ CHIL-BYL® CP-76

Version 1.0 Revision Date 12/22/2020

Flash point : 39 °CMethod: Pensky-Martens closed cup

Evaporation rate : is not determined

Upper explosion limit : Upper flammability limit

is not determined

Lower explosion limit : Lower flammability limit

is not determined

Density : 10.2 - 10.8 lb/gal

Solubility(ies)

Water solubility : is not determined

Partition coefficient: n- : No data available

octanol/water

Autoignition temperature : is not determined

Viscosity

Viscosity, kinematic : is not determined

VOC, less water, in g/l : 356

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Hazardous polymerization does not occur.

Conditions to avoid : Heat, flames and sparks.

Hazardous decomposition

products

: Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method



Childers™ CHIL-BYL® CP-76

Version 1.0 Revision Date 12/22/2020

Components:

toluene:

Acute oral toxicity : LD50 Oral Rat: 5,580 mg/kg

Acute inhalation toxicity : LC50 Rat: 12.5 mg/l

Exposure time: 4 h

Solvent naphtha (petroleum), light arom.:

Acute inhalation toxicity : LC50 Rat: > 5.2 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Dermal Rabbit: > 2,000 mg/kg

1,2,4-trimethylbenzene:

Acute oral toxicity : LD50 Oral Rat: 3,400 mg/kg

Acute inhalation toxicity : LC50 Rat: 18 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal Rabbit: > 3,160 mg/kg

cumene:

Acute oral toxicity : LD50 Oral Rat: 1,400 mg/kg

ethylbenzene:

Acute oral toxicity : LD50 Oral Rat: 3,500 mg/kg

Acute inhalation toxicity : LC50 Rat: 17.2 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity



Childers™ CHIL-BYL® CP-76

Version 1.0 Revision Date 12/22/2020

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

toluene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.8 mg/l

Exposure time: 96 h

Test Method: semi-static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 5.46 - 9.83 mg/l

Exposure time: 48 h Test Method: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (microalgae)): 12.5

mg/l

Exposure time: 72 h Test Type: static test

Solvent naphtha (petroleum), light arom. :

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 9.22 mg/l

Exposure time: 96 h Test Method: static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 6.14 mg/l

Exposure time: 48 h
Test Method: static test

1,2,4-trimethylbenzene:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 7.19 - 8.28

mg/l

Exposure time: 96 h



Childers™ CHIL-BYL® CP-76

Version 1.0 Revision Date 12/22/2020

Test Method: flow-through test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 6.14 mg/l

Exposure time: 48 h
Test Method: static test

tris(nonylphenyl) phosphite:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 10 mg/l

Exposure time: 96 h
Test Method: static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 0.42 mg/l

Exposure time: 48 h Test Method: static test

cumene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.7 mg/l

Exposure time: 96 h

Test Method: semi-static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 0.6 mg/l

Exposure time: 48 h Test Method: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (microalgae)): 2.6 mg/l

Exposure time: 72 h

Test Type: flow-through test

naphthalene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.91 - 2.82 mg/l

Exposure time: 96 h Test Method: static test

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 1.09 - 3.4 mg/l

Exposure time: 48 h Test Method: static test

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): 0.4 mg/l

Exposure time: 72 h

Test Type: flow-through test

Persistence and degradability

No data available

Bioaccumulative potential

Mobility in soil

No data available



Childers™ CHIL-BYL® CP-76

Version 1.0 Revision Date 12/22/2020

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : This product meets the definition of hazardous waste under

the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial

authorities for more restrictive requirements.

The hazard and precautionary statements displayed on the

label also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION

Special precautions for user

Not applicable

Domestic regulation

49 CFR

Not regulated as a dangerous good

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Respiratory or skin sensitization

Germ cell mutagenicity Reproductive toxicity Aspiration hazard



Childers™ CHIL-BYL® CP-76

Version 1.0 Revision Date 12/22/2020

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 302 : This material does not contain any components with a section 302

EHS TPQ.

SARA 313 : The following components are subject to reporting levels established

by SARA Title III, Section 313:

toluene 108-88-3
1,2,4-trimethylbenzene 95-63-6
cumene 98-82-8
ethylbenzene 100-41-4
naphthalene 91-20-3

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

toluene 108-88-3 cumene 98-82-8 ethylbenzene 100-41-4 naphthalene 91-20-3

US State Regulations

California Prop 65 Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

TSCA
All substances listed as active on the TSCA inventory
DSL
AlCS
On the inventory, or in compliance with the inventory
ENCS
On the inventory, or in compliance with the inventory
KECI
On the inventory, or in compliance with the inventory
On the inventory, or in compliance with the inventory
On the inventory, or in compliance with the inventory
IECS
On the inventory, or in compliance with the inventory
IECSC

Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AICS (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV

(Taiwan)

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Department - phone: 1-651-236-5842 - email: msds.request@hbfuller.com




Childers™ CHIL-BYL® CP-76

Version 1.0

Revision Date 12/22/2020

Further information



Special hazard

HMIS III:

HEALTH	3*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.