

# Foster® WEATHERITE™ 46-50

Version 1.1 Revision Date 09/06/2023

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Foster® WEATHERITE™ 46-50

Product code : 100000014972

Manufacturer or supplier's details

Company : H.B. Fuller Construction Products

Address : 1105 South Frontenac

Aurora, IL, 60504

Telephone : 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

### Recommended use of the chemical and restrictions on use

Recommended use : Water based sealant

Restrictions on use : For industrial use only.

#### **SECTION 2. HAZARDS IDENTIFICATION**

### **Emergency Overview**

Appearance	liquid
Color	white
Odor	sweet

### **GHS Classification**

Not a hazardous substance or mixture.

#### **GHS** label elements

Not a hazardous substance or mixture.

#### **Potential Health Effects**

### Carcinogenicity:

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or



# Foster® WEATHERITE™ 46-50

Version 1.1 Revision Date 09/06/2023

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### **Hazardous ingredients**

Chemical name	CAS-No.	Concentration [%]
Proprietary	21645-51-2	10 - 20
Limestone	1317-65-3	10 - 20
Titanium dioxide	13463-67-7	1 - 5
Cellulose	9004-34-6	1 - 5

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : Show this material safety data sheet to the doctor in

attendance.

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.

In case of eye contact : Flush eyes with water at least 15 minutes. Get medical

attention if eye irritation develops or persists.

If swallowed : Do not induce vomiting. Seek medical attention if symptoms

develop. Provide medical care provider with this SDS.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Not combustible.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: none

Specific hazards during fire

fighting

: Cool closed containers exposed to fire with water spray.

Specific extinguishing

methods

Further information : This product is an aqueous mixture that will not burn. Dried



# Foster® WEATHERITE™ 46-50

Version 1.1 Revision Date 09/06/2023

product film will burn in a fire.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.

Environmental precautions : No special environmental precautions required.

Prevent product from entering drains.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : No special precautions are needed in handling this material.

Conditions for safe storage : Keep container closed when not in use.

Keep in a dry, cool place.

Materials to avoid : Do not freeze.

No special restrictions on storage with other products.

Storage temperature :  $>= 40 \, ^{\circ}F$ 

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Proprietary	21645-51-2	TWA (Respirable particulate matter)	1 mg/m3	ACGIH
		TWA (Respirable particulate matter)	1 mg/m3	ACGIH
Limestone	1317-65-3	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA	5 mg/m3	NIOSH REL



# Foster® WEATHERITE™ 46-50

Version 1.1

Revision Date 09/06/2023

	I	(Respirable)		
		TWA (total)	10 mg/m3	NIOSH REL
		TWA	5 mg/m3	NIOSH REL
		(Respirable)		
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total	15 mg/m3	OSHA Z-1
		dust) `		
		TWÁ	5 mg/m3	OSHA Z-1
		(respirable		
		fraction)		
		TWA (Total)	15 mg/m3	OSHA P0
		TWA	5 mg/m3	OSHA P0
		(Respirable		
		fraction)		
		TWA (Total	15 mg/m3	OSHA P0
		dust)	_	
		TWA	5 mg/m3	OSHA P0
		(respirable		
		dust fraction)		
Titanium dioxide	13463-67-7	TWA	10 mg/m3	ACGIH
		TWA (total	15 mg/m3	OSHA Z-1
		dust)		
		TWA (Total)	10 mg/m3	OSHA P0
		TWA (Total	10 mg/m3	OSHA P0
		dust)		
Cellulose	9004-34-6	TWA	10 mg/m3	ACGIH
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA Z-1
		(respirable	3 mg/m3	0011A Z-1
		fraction)		
		TWA (Total)	15 mg/m3	OSHA P0
		TWA	5 mg/m3	OSHA P0
		(Respirable	3 mg/m3	OOHATO
		fraction)		
		TWA (Total	15 mg/m3	OSHA P0
		dust)	10 mg/mo	00111110
		TWA	5 mg/m3	OSHA P0
		(respirable	o mg/mo	001
		dust fraction)		
		PEL (Total	10 mg/m3	CAL PEL
		dust)		
		PEL	5 mg/m3	CAL PEL
		(respirable		
		dust fraction)		

# Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.



# Foster® WEATHERITE™ 46-50

Version 1.1 Revision Date 09/06/2023

In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection

Material : Nitrile rubber

Remarks : For prolonged or repeated contact use protective gloves.

Eye protection : Safety glasses

Protective measures : No special protective equipment required.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid Color : white Odor : sweet

Odor Threshold : no data available

Melting point/freezing point : 32 °F Boiling point/boiling range : 212 °F

Flash point : Not applicable Evaporation rate : is not determined

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit : Upper flammability limit

is not determined

Lower explosion limit : Lower flammability limit

is not determined

Vapor pressure : is not determined Relative vapor density : is not determined

Density : 11.3 lb/gal

Solubility(ies)

Water solubility : dispersible

Partition coefficient: n- : no data available

octanol/water

Autoignition temperature : is not determined

VOC, less water, in g/l : 1

#### **SECTION 10. STABILITY AND REACTIVITY**

Chemical stability : The product is chemically stable.



# Foster® WEATHERITE™ 46-50

Version 1.1 Revision Date 09/06/2023

Possibility of hazardous

reactions

Hazardous decomposition

products

: Hazardous polymerization does not occur.

: Stable under normal conditions.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

### **Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l

Exposure time: 4 Hours
Test atmosphere: dust/mist
Method: Calculation method

### **Components:**

Cellulose:

Acute inhalation toxicity : LC50 Rat: > 5.800 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

#### Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available



# Foster® WEATHERITE™ 46-50

Version 1.1

Revision Date 09/06/2023

### STOT-repeated exposure

No data available

### **Aspiration toxicity**

No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

No data available

Persistence and degradability

No data available

**Bioaccumulative potential** 

Mobility in soil

No data available

Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

### **SECTION 14. TRANSPORT INFORMATION**

### International Regulations

## UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good



# Foster® WEATHERITE™ 46-50

Version 1.1

Revision Date 09/06/2023

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**Domestic regulation** 

49 CFR

Not regulated as a dangerous good

### **SECTION 15. REGULATORY INFORMATION**

SARA 311/312 Hazards : No SARA Hazards

**SARA 302** : This material does not contain any components with a section 302

EHS TPQ.

SARA 313 : This material does not contain any chemical components with known

CAS numbers that exceed the threshold (De Minimis) reporting levels

established by SARA Title III, Section 313.

### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

**US State Regulations** 

**California Prop 65** Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

TSCA All substances listed as active on the TSCA inventory

All components of this product are on the Canadian DSL Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AllC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

# **SECTION 16. OTHER INFORMATION**

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com




# Foster® WEATHERITE™ 46-50

Version 1.1

Revision Date 09/06/2023

### **Further information**



Special hazard

#### HMIS III:

HEALTH	0/
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.