

SAFETY DATA SHEET**Foster® FOAMSEAL™ 30-45N**

Version 1.1

Revision Date 02/24/2023

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Foster® FOAMSEAL™ 30-45N
Product code : 100000015209

Manufacturer or supplier's details

Company : H.B. Fuller Company
Address : 1200 Willow Lake Boulevard
Vadnais Heights, MN 55110
Telephone : 1-888-423-8553
Medical Emergency Phone Number (24 Hours): 1-888-853-1758
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Solvent based adhesive
Restrictions on use : For industrial use only.


SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance	liquid
Color	gray
Odor	solvent

GHS Classification

Skin sensitization : Category 1
Germ cell mutagenicity : Category 1B

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements:

H317 May cause an allergic skin reaction. H340 May cause genetic defects.

Precautionary Statements:

Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/

SAFETY DATA SHEET**Foster® FOAMSEAL™ 30-45N**

Version 1.1

Revision Date 02/24/2023

spray. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P363 Wash contaminated clothing before reuse.

Storage: P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects**Carcinogenicity:****IARC**

Group 1: Carcinogenic to humans During normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.

Quartz (SiO₂) 14808-60-7

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

Known to be human carcinogen During normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.

Quartz (SiO₂) 14808-60-7

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
Calcium carbonate	471-34-1	50 - 70
Stoddard solvent	8052-41-3	1 - 5
Quartz (SiO ₂)	14808-60-7	0.1 - 1
Solvent naphtha (petroleum), light arom.	64742-95-6	0.1 - 1
cobalt bis(2-ethylhexanoate)	136-52-7	0.1 - 1
butanone oxime	96-29-7	0.1 - 1
Distillates (petroleum), hydrotreated light	64742-47-8	0.1 - 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Show this material safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.

SAFETY DATA SHEET**Foster® FOAMSEAL™ 30-45N**

Version 1.1

Revision Date 02/24/2023

-
- Get medical attention if irritation develops and persists.
- In case of eye contact : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : Do NOT induce vomiting.
If victim is fully conscious, give a cupful of water.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Prevent spreading over a wide area (e.g., by containment or oil barriers).
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
Sweep up and shovel into suitable containers for disposal.
Non-sparking tools should be used.
-

SECTION 7. HANDLING AND STORAGE

- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Avoid inhalation of vapor or mist.
Do not use in areas without adequate ventilation.
Keep away from fire, sparks and heated surfaces.
Keep container closed when not in use.
Take precautionary measures against static discharges.
-

SAFETY DATA SHEET
Foster® FOAMSEAL™ 30-45N

Version 1.1

Revision Date 02/24/2023

- Conditions for safe storage : Take measures to prevent the build up of electrostatic charge.
 Use explosion-proof equipment.
 Keep containers tightly closed in a dry, cool and well-ventilated place.
 Keep away from sources of ignition - No smoking.
 Solvent vapors are heavier than air and may spread along floors.
- Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium carbonate	471-34-1	PEL (Total dust)	10 mg/m ³	CAL PEL
		PEL (respirable dust fraction)	5 mg/m ³	CAL PEL
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m ³	NIOSH REL
		C	1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,900 mg/m ³	OSHA Z-1
		TWA	100 ppm 525 mg/m ³	OSHA P0
Quartz (SiO ₂)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (total dust)	30 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m ³	CAL PEL

SAFETY DATA SHEET
Foster® FOAMSEAL™ 30-45N

Version 1.1

Revision Date 02/24/2023

		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	200 mg/m ³	ACGIH
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	200 mg/m ³	ACGIH
		TWA	400 ppm 1,600 mg/m ³	OSHA P0

Engineering measures : Use local exhaust ventilation or other engineering controls to minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapor Type

Hand protection
Material : Nitrile rubber

Eye protection : Safety glasses with side-shields

Hygiene measures : Avoid contact with skin, eyes and clothing.
Provide adequate ventilation.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
 Color : gray
 Odor : solvent
 Odor Threshold : no data available
 pH : Not applicable
 Melting point/freezing point : is not determined
 Boiling point/boiling range : is not determined
 Flash point : > 142 °F
 Evaporation rate : is not determined
 Upper explosion limit : Upper flammability limit
 is not determined

SAFETY DATA SHEET

Foster® FOAMSEAL™ 30-45N

Version 1.1

Revision Date 02/24/2023

Lower explosion limit	:	Lower flammability limit is not determined
Vapor pressure	:	is not determined
Density	:	13.2 - 14.2 lb/gal
Solubility(ies)	:	
Water solubility	:	is not determined
Partition coefficient: n-octanol/water	:	no data available
Autoignition temperature	:	is not determined
Viscosity	:	
Viscosity, kinematic	:	is not determined

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Hazardous polymerization does not occur.
Conditions to avoid	:	Heat, flames and sparks.
Hazardous decomposition products	:	Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute inhalation toxicity	:	Acute toxicity estimate : > 200 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
---------------------------	---	--

Components:**Solvent naphtha (petroleum), light arom.:**

Acute inhalation toxicity	:	LC50 Rat: > 5.2 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	:	LD50 Dermal Rabbit: > 2,000 mg/kg

butanone oxime:

Acute oral toxicity	:	LD50 Oral Rat: 930 mg/kg
---------------------	---	--------------------------

SAFETY DATA SHEET**Foster® FOAMSEAL™ 30-45N**

Version 1.1

Revision Date 02/24/2023

Distillates (petroleum), hydrotreated light:

Acute inhalation toxicity : LC50 Rat: > 5.2 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicityNo data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Solvent naphtha (petroleum), light arom. :**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 9.22 mg/l
Exposure time: 96 h
Test Method: static test

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 6.14 mg/l
aquatic invertebrates : Exposure time: 48 h
Test Method: static test

SAFETY DATA SHEET**Foster® FOAMSEAL™ 30-45N**

Version 1.1

Revision Date 02/24/2023

butanone oxime :

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 320 - 1,000 mg/l
Exposure time: 96 h
Test Method: static test

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 83 mg/l
Exposure time: 72 h
Test Type: flow-through test

Distillates (petroleum), hydrotreated light :

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 2.2 mg/l
Exposure time: 96 h
Test Method: static test

Persistence and degradability

No data available

Bioaccumulative potential**Mobility in soil**

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements. The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

SAFETY DATA SHEET**Foster® FOAMSEAL™ 30-45N**

Version 1.1

Revision Date 02/24/2023

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**SARA 311/312 Hazards** : Respiratory or skin sensitization
Germ cell mutagenicity**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

cobalt bis(2-ethylhexanoate) 136-52-7

US State Regulations**California Prop 65** Please contact Supplier for more information.**The ingredients of this product are reported in the following inventories:****TSCA** All substances listed as active on the TSCA inventory**DSL** All components of this product are on the Canadian DSL**AIIC** On the inventory, or in compliance with the inventory**ENCS** On the inventory, or in compliance with the inventory**KECI** On the inventory, or in compliance with the inventory**PICCS** On the inventory, or in compliance with the inventory**IECSC** On the inventory, or in compliance with the inventory**Inventories Legend** TSCA (USA), DSL (Canada), REACH(Europe), AIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)


SAFETY DATA SHEET
Foster® FOAMSEAL™ 30-45N

Version 1.1

Revision Date 02/24/2023

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

Further information
NFPA:

HMIS III:

HEALTH	2*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.