

SAFETY DATA SHEET**Foster® VAPOR-FAS™ 30-65**

Version 1.3

Revision Date 08/22/2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Foster® VAPOR-FAS™ 30-65
Product code : 100000014998

Manufacturer or supplier's details

Company : H.B. Fuller Construction Products

Address : 1105 South Frontenac
Aurora, IL, 60504

Telephone : 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Water based sealant

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance	liquid
Color	white
Odor	ammoniacal

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Potential Health Effects**Carcinogenicity:**

IARC Group 2B: Possibly carcinogenic to humans
Paraffin waxes and Hydrocarbon waxes, chloro 63449-39-8
Alkanes, chloro 61788-76-9

SAFETY DATA SHEET
Foster® VAPOR-FAS™ 30-65

Version 1.3

Revision Date 08/22/2024

Attapulgit

12174-11-7

OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reasonably anticipated to be a human carcinogen

Paraffin waxes and

63449-39-8

Hydrocarbon waxes, chloro

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
aluminium hydroxide	21645-51-2	20 - 30
kaolin	1332-58-7	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Wollastonite (Ca(SiO ₃))	13983-17-0	1 - 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
If symptoms persist, call a physician.
- In case of skin contact : Wash off with soap and water.
- In case of eye contact : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.

SAFETY DATA SHEET

Foster® VAPOR-FAS™ 30-65

Version 1.3

Revision Date 08/22/2024

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Not combustible.
 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : none
- Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.
- Specific extinguishing methods :
- Further information : This product is an aqueous mixture that will not burn. Dried product film will burn in a fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : No special environmental precautions required.
 Prevent product from entering drains.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : No special precautions are needed in handling this material.
- Conditions for safe storage : Keep container closed when not in use.
 Keep in a dry, cool place.
- Materials to avoid : Do not freeze.
 No special restrictions on storage with other products.
- Storage temperature : ≥ 40 °F

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
------------	---------	------------	---------	-------

SAFETY DATA SHEET
Foster® VAPOR-FAS™ 30-65

Version 1.3

Revision Date 08/22/2024

		(Form of exposure)	parameters / Permissible concentration	
aluminium hydroxide	21645-51-2	TWA (Respirable particulate matter)	1 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	1 mg/m ³	ACGIH
kaolin	1332-58-7	TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Total)	10 mg/m ³	OSHA P0
		TWA (Respirable fraction)	5 mg/m ³	OSHA P0
		TWA (Total dust)	10 mg/m ³	OSHA P0
		TWA (respirable dust fraction)	5 mg/m ³	OSHA P0
Titanium dioxide	13463-67-7	TWA	10 mg/m ³	ACGIH
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (Total)	10 mg/m ³	OSHA P0
		TWA (Total dust)	10 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	0.2 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	2.5 mg/m ³	ACGIH
Wollastonite (Ca(SiO ₃))	13983-17-0	TWA (Inhalable particulate matter)	1 mg/m ³	ACGIH

Personal protective equipment

SAFETY DATA SHEET**Foster® VAPOR-FAS™ 30-65**

Version 1.3

Revision Date 08/22/2024

Respiratory protection	: No personal respiratory protective equipment normally required. In case of insufficient ventilation, wear suitable respiratory equipment.
Hand protection	
Material	: Nitrile rubber
Remarks	: For prolonged or repeated contact use protective gloves.
Eye protection	: Safety glasses
Protective measures	: No special protective equipment required.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: white
Odor	: ammoniacal
Odor Threshold	: no data available
Melting point/freezing point	: 32 °F
Boiling point/boiling range	: 212 °F
Flash point	: Not applicable
Evaporation rate	: is not determined
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: Upper flammability limit is not determined
Lower explosion limit	: Lower flammability limit is not determined
Vapor pressure	: is not determined
Relative vapor density	: is not determined
Density	: 11.1000 lb/gal
Solubility(ies)	
Water solubility	: dispersible
Partition coefficient: n-octanol/water	: no data available
Autoignition temperature	: is not determined
VOC, less water, in g/l	: 38

SECTION 10. STABILITY AND REACTIVITY

SAFETY DATA SHEET**Foster® VAPOR-FAS™ 30-65**

Version 1.3

Revision Date 08/22/2024

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Hazardous polymerization does not occur.

Hazardous decomposition products : Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

SAFETY DATA SHEET**Foster® VAPOR-FAS™ 30-65**

Version 1.3

Revision Date 08/22/2024

Persistence and degradability

No data available

Bioaccumulative potential**Mobility in soil**

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.
The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Alkanes, C14-17, Chloro)
Class : 9
Packing group : III
Labels : Miscellaneous,
Packing instruction (cargo aircraft) : 956
Packing instruction (passenger aircraft) : 956
Remarks : PACKAGES <5 L NOT REGULATED, IATA 4.4, SP A197

IMDG-Code

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(Alkanes, C14-17, Chloro)
Class : 9
Subsidiary risk : ENVIRONM.
Packing group : III
Labels : 9 (ENVIRONM.)
EmS Code : F-A, S-F

SAFETY DATA SHEET**Foster® VAPOR-FAS™ 30-65**

Version 1.3

Revision Date 08/22/2024

Marine pollutant : yes
Remarks : PACKAGES <5 L NOT REGULATED, IMDG 3.3 SP 969

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

Remarks : Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : No SARA Hazards

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

US State Regulations

California Prop 65 Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

TCSI Not in compliance with the inventory
TSCA All substances listed as active on the TSCA inventory
AIRC Not in compliance with the inventory

SAFETY DATA SHEET
Foster® VAPOR-FAS™ 30-65


Version 1.3

Revision Date 08/22/2024

DSL	All components of this product are on the Canadian DSL
ENCS	Not in compliance with the inventory
ISHL	Not in compliance with the inventory
KECI	On the inventory, or in compliance with the inventory
PICCS	On the inventory, or in compliance with the inventory
IECSC	On the inventory, or in compliance with the inventory
NZIoC	Not in compliance with the inventory
CHINV	The mixture contains substances listed on the Swiss Inventory
REACH	Not in compliance with the inventory
	Not in compliance with the inventory
	Not in compliance with the inventory
TECI	Not in compliance with the inventory
Inventories Legend	TSCA (USA), DSL (Canada), REACH(Europe), AIIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

Further information
NFPA:

HMIS III:

HEALTH	0/
FLAMMABILITY	1
PHYSICAL HAZARD	0

 0 = not significant, 1 =Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.