

# Foster® INTERIOR DEFENSE® 40-50

Version 1.0 Revision Date 12/22/2020

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Foster® INTERIOR DEFENSE® 40-50

Product code : 100000015215

Manufacturer or supplier's details

Company : H.B. Fuller Construction Products

Address : 1105 South Frontenac

Aurora, IL, 60504

Telephone : 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Water based sealant

Restrictions on use : For industrial use only.

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

| Appearance | liquid |
|------------|--------|
| Color      | white  |
| Odor       | sweet  |

# **GHS Classification**

Skin sensitization : Category 1

**GHS** label elements

Hazard pictograms

Signal Word : Warning

**Hazard Statements:** 

H317 May cause an allergic skin reaction.

**Precautionary Statements:** 

**Prevention:** P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves.



# Foster® INTERIOR DEFENSE® 40-50

Version 1.0 Revision Date 12/22/2020

**Response:** P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P363 Wash contaminated clothing before

**Disposal:** P501 Dispose of contents/ container to an approved waste disposal plant.

**Potential Health Effects** 

Carcinogenicity:

IARC Group 2B: Possibly carcinogenic to humans During normal handling

of the product, this substance is encapsulated within the product

and will not present a cancer exposure risk.

titanium dioxide 13463-67-7

**OSHA**No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens. No ingredient of this product present at levels greater than or

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

# **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

# Hazardous ingredients

| Chemical name                    | CAS-No.    | Concentration [%] |
|----------------------------------|------------|-------------------|
| barium diboron tetraoxide        | 13701-59-2 | 5 - 10            |
| titanium dioxide                 | 13463-67-7 | 5 - 10            |
| zinc oxide                       | 1314-13-2  | 1 - 5             |
| 3-iodo-2-propynyl butylcarbamate | 55406-53-6 | 0.1 - 1           |

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : Show this material safety data sheet to the doctor in

attendance.

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.

In case of eye contact : Flush eyes with water at least 15 minutes. Get medical

attention if eye irritation develops or persists.

If swallowed : Do not induce vomiting. Seek medical attention if symptoms

develop. Provide medical care provider with this SDS.



# Foster® INTERIOR DEFENSE® 40-50

Version 1.0 Revision Date 12/22/2020

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Not combustible.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: none

Specific hazards during fire

fighting

: Cool closed containers exposed to fire with water spray.

Specific extinguishing

methods

Further information

: This product is an aqueous mixture that will not burn. Dried

product film will burn in a fire.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.

Environmental precautions

: No special environmental precautions required.

Prevent product from entering drains.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : No special precautions are needed in handling this material.

Conditions for safe storage : Keep container closed when not in use.

Keep in a dry, cool place.

Materials to avoid : Do not freeze.

No special restrictions on storage with other products.

Storage temperature : >= 40 °F

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Ingredients with workplace control parameters



# Foster® INTERIOR DEFENSE® 40-50

Version 1.0 Revision Date 12/22/2020

| Components                | CAS-No.    | Value type                 | Control             | Basis     |
|---------------------------|------------|----------------------------|---------------------|-----------|
| Components                | OAO NO.    | (Form of                   | parameters /        | Dasis     |
|                           |            | exposure)                  | Permissible         |           |
|                           |            | , ,                        | concentration       |           |
| barium diboron tetraoxide | 13701-59-2 | TWA                        | 0.5 mg/m3           | OSHA Z-1  |
|                           |            | TWA                        | 0.5 mg/m3           | ACGIH     |
|                           |            | TWA                        | 0.5 mg/m3           | OSHA P0   |
|                           |            | TWA                        | 0.5 mg/m3           | OSHA Z-1  |
|                           |            | TWA                        | 0.5 mg/m3           | ACGIH     |
|                           |            | TWA                        | 0.5 mg/m3           | OSHA P0   |
|                           |            | TWA                        | 0.5 mg/m3           | NIOSH REL |
| titanium dioxide          | 13463-67-7 | TWA                        | 10 mg/m3            | ACGIH     |
|                           |            | TWA (total dust)           | 15 mg/m3            | OSHA Z-1  |
|                           |            | TWA (Total)                | 10 mg/m3            | OSHA P0   |
|                           |            | TWA (Total dust)           | 10 mg/m3            | OSHA P0   |
| zinc oxide                | 1314-13-2  | TWA                        | 2 mg/m3             | ACGIH     |
|                           |            | (Respirable                |                     |           |
|                           |            | particulate                |                     |           |
|                           |            | matter)                    | 10 / 0              | 100111    |
|                           |            | STEL                       | 10 mg/m3            | ACGIH     |
|                           |            | (Respirable particulate    |                     |           |
|                           |            | matter)                    |                     |           |
|                           |            | TWA                        | 5 mg/m3             | OSHA Z-1  |
|                           |            | (Fumes)                    | 5g,                 |           |
|                           |            | TWA (total                 | 15 mg/m3            | OSHA Z-1  |
|                           |            | dust) `                    |                     |           |
|                           |            | TWÁ                        | 5 mg/m3             | OSHA Z-1  |
|                           |            | (respirable                |                     |           |
|                           |            | fraction)                  |                     |           |
|                           |            | TWA (Total)                | 10 mg/m3            | OSHA P0   |
|                           |            | TWA                        | 5 mg/m3             | OSHA P0   |
|                           |            | (Respirable                |                     |           |
|                           |            | fraction) TWA              | 5 mg/m2             | OSHA P0   |
|                           |            | STEL                       | 5 mg/m3<br>10 mg/m3 | OSHA PO   |
|                           |            | TWA (Total                 | 10 mg/m3            | OSHA PO   |
|                           |            | dust) `                    | J                   |           |
|                           |            | TWA                        | 5 mg/m3             | OSHA P0   |
|                           |            | (respirable dust fraction) |                     |           |
|                           |            | TWA<br>(Fumes)             | 5 mg/m3             | OSHA P0   |
|                           |            | STEL<br>(Fumes)            | 10 mg/m3            | OSHA P0   |
|                           | •          | ,                          | •                   | •         |

Personal protective equipment



# Foster® INTERIOR DEFENSE® 40-50

Version 1.0 Revision Date 12/22/2020

Respiratory protection : No personal respiratory protective equipment normally

required.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection

Material : Nitrile rubber

Remarks : For prolonged or repeated contact use protective gloves.

Eye protection : Safety glasses

Protective measures : No special protective equipment required.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid
Color : white
Odor : sweet

Odor Threshold : No data available

Melting point/freezing point : 32 °F Boiling point/boiling range : 212 °F

Evaporation rate : is not determined

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit : Upper flammability limit

is not determined

Lower explosion limit : Lower flammability limit

is not determined

Relative vapor density : is not determined

Density : 11.4 - 12.2 lb/gal

Solubility(ies)

Water solubility : dispersible

Partition coefficient: n-

octanol/water

: No data available

Autoignition temperature : is not determined

VOC, less water, in g/l : 38.1

# **SECTION 10. STABILITY AND REACTIVITY**

Chemical stability : The product is chemically stable.

Possibility of hazardous : Hazardous polymerization does not occur.



# Foster® INTERIOR DEFENSE® 40-50

Version 1.0 Revision Date 12/22/2020

reactions

Hazardous decomposition

products

: Stable under normal conditions.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

**Product:** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 122.17 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

**Aspiration toxicity** 

No data available



# Foster® INTERIOR DEFENSE® 40-50

Version 1.0

Revision Date 12/22/2020

## **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

No data available

Persistence and degradability

No data available

**Bioaccumulative potential** 

Mobility in soil

No data available

Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

Waste from residues : To the best of our knowledge, this product does not meet the

definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities

for more restrictive requirements.

The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

# **SECTION 14. TRANSPORT INFORMATION**

# Special precautions for user

Not applicable

#### **Domestic regulation**

**49 CFR** 

Not regulated as a dangerous good

# **International Regulations**

IATA-DGR

UN/ID No. : 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(ALKANES, C14-17, CHLORO)

Class : 9



# Foster® INTERIOR DEFENSE® 40-50

Version 1.0 Revision Date 12/22/2020

Packing group : III
Labels : 9
Packing instruction (cargo : 964

aircraft)

Packing instruction : 964

(passenger aircraft)

**IMDG-Code** 

UN number : 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(ALKANES, C14-17, CHLORO)

Class : 9
Packing group : III
Labels : 9

EmS Code : F-A, S-F Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **SECTION 15. REGULATORY INFORMATION**

SARA 311/312 Hazards : Respiratory or skin sensitization

**SARA 302** : This material does not contain any components with a section 302

EHS TPQ.

**SARA 313** : The following components are subject to reporting levels established

by SARA Title III, Section 313:

barium diboron tetraoxide 13701-59-2 zinc oxide 1314-13-2 150 Not Assigned

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

**US State Regulations** 

California Prop 65 Please contact Supplier for more information.



# Foster® INTERIOR DEFENSE® 40-50

Version 1.0 Revision Date 12/22/2020

#### The ingredients of this product are reported in the following inventories:

TSCA

All substances listed as active on the TSCA inventory

All components of this product are on the Canadian DSL

AICS

On the inventory, or in compliance with the inventory

ENCS

On the inventory, or in compliance with the inventory

On the inventory, or in compliance with the inventory

IECSC

On the inventory, or in compliance with the inventory

Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AICS (Australia), NZIoC

(New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV


(Taiwan)

#### **SECTION 16. OTHER INFORMATION**

Prepared by: Global Regulatory Department - phone: 1-651-236-5842 - email: msds.reguest@hbfuller.com

#### **Further information**





# HMIS III:



0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.