

SAFETY DATA SHEET

REVISION DATE: 06-23-2020

SUPERSEDES: 02-11-2020

SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER**PRODUCT INFORMATION**

PRODUCT: FOSTER 85-20
PRODUCT DESCRIPTION: Adhesive
INTENDED USE: Adhesive
PRODUCT IDENTIFIER: 802414PM

COMPANY INFORMATION

H.B. Fuller Construction Products Inc.
1105 S. Frontenac Street
Aurora, IL 60504
Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION**GHS Hazard Symbols:****GHS Signal Word:** Warning**GHS Classification:** Skin Sensitisation Category 1; Skin Corrosion/Irritation Category 2; Serious Eye Damage/Eye Irritation Category 2; Carcinogenicity Category 2; Hazardous to the aquatic environment - Chronic Category 2; Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3; Hazardous to the aquatic environment - Acute Category 3; Additional category for effects on or via lactation**GHS Hazard Phrases:** Causes skin irritation.; May cause an allergic skin reaction.; Causes serious eye irritation.; May cause respiratory irritation.; May cause drowsiness or dizziness.; Suspected of causing cancer.; May cause harm to breast-fed children.; Harmful to aquatic life.; Toxic to aquatic life with long lasting effects.**GHS Precautions:****Safety Precautions:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.**First Aid Measures:** IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. P362+P364 - Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. Collect spillage.**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store locked up.

SAFETY DATA SHEET

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulation for chemical wastes.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	PERCENT	Classification	Note
Methylene chloride	75-09-2	50 - 70	Acute Tox. 4; H302 Eye Irrit. 2; H319 Skin Irrit. 2; H315 STOT SE 3; H335, H336	
Chlorinated paraffin	63449-39-8	10 - 30	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Effects on or via lactation; H362	
Ethyl alcohol	64-17-5	1 - 5	Eye Irrit. 2; H319	
Titanium dioxide	13463-67-7	0.1 - 1	Carc. 2; H351	* (see below)
Stoddard solvent	8052-41-3	0.1 - 1		
Tri(nonylphenol)phosphite	26523-78-4	0.1 - 1	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Skin Sens. 1; H317	

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

IF IN EYES: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Restore breathing, if necessary. Keep warm and quiet. Call a physician.

IF SWALLOWED: Severely irritating. Do not induce vomiting. Seek medical attention immediately. Drink 2 glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:

Use water spray, foam, dry chemical or carbon dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

There is a possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers.

SPECIAL FIRE FIGHTING INSTRUCTIONS:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS:

Carbon dioxide, Carbon monoxide Chlorine containing gases

SAFETY DATA SHEET

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred.

METHODS FOR CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Avoid breathing vapors.
Use only with adequate ventilation.
Avoid contact with eyes, skin and clothing.
Wash thoroughly after handling.
Keep container closed.
Emptied container retains vapor and product residue.
Observe all labeled safeguards until container is cleaned.
DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.
Aluminum is not an acceptable material of construction for pumps, mixers, fittings or storage for this product.

Storage: Store in a cool, dry place.
Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS:

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Methylene chloride		50 ppm TWA	25 ppm TWA 125 ppm STEL (see 29 CFR 1910.1052)
Calcium carbonate	* (see below)	No data available.	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)
Toluene		20 ppm TWA	200 ppm TWA 300 ppm Ceiling
Ethyl alcohol		No data available. 1000 ppm STEL	1000 ppm TWA; 1900 mg/m ³ TWA
Titanium dioxide	* (see below)	10 mg/m ³ TWA	15 mg/m ³ TWA (total dust)
Stoddard solvent		100 ppm TWA	500 ppm TWA; 2900 mg/m ³ TWA
Methyl isobutyl ketone		20 ppm TWA 75 ppm STEL	100 ppm TWA; 410 mg/m ³ TWA
Methyl alcohol		200 ppm TWA 250 ppm STEL	200 ppm TWA; 260 mg/m ³ TWA

SAFETY DATA SHEET

		Skin absorption may potentially contribute to the overall exposure to this material.	
--	--	--	--

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

ENGINEERING CONTROL METHODS:

VENTILATION:	Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.
EYE PROTECTION:	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
SKIN PROTECTION:	Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt. An apron may be appropriate if splashing can occur. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption so that the TLV is not invalidated.
GLOVES:	Nitrile
RESPIRATORY PROTECTION:	Respiratory protection will be required when ventilation or other engineering controls can not reduce the exposure to acceptable levels. Use supplied-air respiratory equipment as required. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Liquid
COLOR:	Off-white
ODOR:	Solvent
ODOR THRESHOLD:	Not established
pH:	Not established
FREEZING/MELTING POINT (deg. C):	Not established
BOILING POINT (deg. C):	Not established
FLASH POINT:	Non flammable
EVAPORATION RATE:	Not established
FLAMMABILITY:	Not a flammable solid or gas
UPPER EXPLOSIVE LIMIT (% in air):	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
VAPOR PRESSURE (mm Hg):	Not established
VAPOR DENSITY:	Not established
WEIGHT PER GALLON (lbs.):	10.80
SPECIFIC GRAVITY:	1.290
SOLUBILITY:	Not established
OCTANOL/WATER COEFFICIENT:	Not established
AUTOIGNITION TEMPERATURE:	Not established
DECOMPOSITION TEMPERATURE:	Not established
VISCOSITY:	No data available.
SOLIDS (% by weight):	43.0
VOC, weight percent	6.15
VOC, U.S. EPA Method 24, less water and exempt	162g/liter of material

SAFETY DATA SHEET

solvents (theoretically determined)

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.
CHEMICAL INCOMPATIBILITY: Aluminum alloys
HAZARDOUS POLYMERIZATION: Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS: Chlorine containing gases Carbon monoxide, carbon dioxide

SECTION 11: TOXICOLOGICAL INFORMATION

Component Toxicity / Toxicology Data:

COMPONENT NAME	LD50/LC50
Methylene chloride	Oral LD50 Rat 1,600 mg/kg INHALATION LC50-6H Rat 53.00 mg/l
Chlorinated paraffin	Oral LD50 Rat > 21,500 microliter/kg
Chlorinated paraffin	Oral LD50 Rat > 21,500 microliter/kg
Toluene	Oral LD50 Rat 636 mg/kg Inhalation LC50 Rat 12.50 mg/l

This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Serious eye damage / irritation :Can cause moderate irritation, tearing and reddening.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that is suspected of causing cancer.

Reproductive toxicity: Contains a substance that is a possible reproductive hazard based on animal studies.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: No data available.

Specific target organ toxicity-repeated exposure: No data available.

Target organs potentially affected by exposure: Heart Liver Central nervous system Reproductive system Blood Lungs Kidneys Eyes

Aspiration hazard: Not an aspiration hazard.

Medical Conditions Aggravated by Exposure: Liver disease, Overexposure to methylene chloride may cause cardiac effects (including the elevation of carboxyhemoglobin levels) which may be significant in smokers or persons with anemia or heart disease and those exposed to carbon monoxide, Blood disorders (like anemia), Lung disease, Kidney disease, Eye disease

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available for this product.
MOBILITY: No data available.
PERSISTENCE: No data available.
BIOACCUMULATION: No data available.

SAFETY DATA SHEET

This product has not been tested for ecological effects. Relevant information for components is listed below:

Component:	Ecotoxicity values:
Methylene chloride	Acute Toxicity (Fish): Not established Acute Toxicity (Daphnia): EC50 Daphnia magna 1532 - 1847 mg/L 48 h; EC50 Daphnia magna 190 mg/L 48 h Acute Toxicity (Algae): EC50 Pseudokirchneriella subcapitata >500 mg/L 96 h; EC50 Pseudokirchneriella subcapitata >500 mg/L 72 h
Chlorinated paraffin	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: >0.0109 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 94.5 - 271 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >0.1 mg/L [flow-through] Acute Toxicity (Daphnia): Not established Acute Toxicity (Algae): Not established
Chlorinated paraffin	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: >0.0109 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 94.5 - 271 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >0.1 mg/L [flow-through] Acute Toxicity (Daphnia): Not established Acute Toxicity (Algae): Not established
Toluene	Acute Toxicity (Fish): LC50 Pimephales promelas 15.22 - 19.05 mg/L 96 h; LC50 Pimephales promelas 12.6 mg/L 96 h; LC50 Oncorhynchus mykiss 5.89 - 7.81 mg/L 96 h; LC50 Oncorhynchus mykiss 14.1 - 17.16 mg/L 96 h; LC50 Oncorhynchus mykiss 5.8 mg/L 96 h; LC50 Lepomis macrochirus 11.0 - 15.0 mg/L 96 h; LC50 Oryzias latipes 54 mg/L 96 h; LC50 Poecilia reticulata 28.2 mg/L 96 h; LC50 Poecilia reticulata 50.87 - 70.34 mg/L 96 h Acute Toxicity (Daphnia): EC50 Daphnia magna 5.46 - 9.83 mg/L 48 h; EC50 Daphnia magna 11.5 mg/L 48 h Acute Toxicity (Algae): 72 Hr EC50 Pseudokirchneriella subcapitata: 12.5 mg/L [static]
Ethyl alcohol	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: 12.0 - 16.0 mL/L [static] Acute Toxicity (Daphnia): 48 Hr EC50 Daphnia magna: 2 mg/L [Static] Acute Toxicity (Algae): Not established

SECTION 13: DISPOSAL CONSIDERATIONS

This product contains greater than 10% chlorinated solvent. Spent chlorinated solvents are considered hazardous waste; however, as a component of a mixture, chlorinated solvents do not meet the RCRA definition of hazardous waste under 40 CFR 261. Consult state, local, or provincial authorities for more restrictive requirements.

LAND DISPOSAL RESTRICTIONS: Methylene chloride Toluene Methyl isobutyl ketone Methanol

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

US DOT: UN1593, DICHLOROMETHANE MIXTURE, 6.1, PGIII.
IATA: UN1593, DICHLOROMETHANE MIXTURE, 6.1, PGIII.
IMDG: UN1593, DICHLOROMETHANE MIXTURE, 6.1, PGIII, EMS F-A, S-A.

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt from DSL requirements.

EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.

AUSTRALIA AICS: This product is in compliance with the Australian Inventory of Chemical Substances requirements.

KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List

SAFETY DATA SHEET

requirements.

PHILIPPINES: This product is in compliance with the Philippine Inventory of Chemicals and Chemical Substances requirements.

CHINA IECSC INVENTORY: This product is in compliance with the Inventory of Existing Chemical Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg.request@hbfuller.com to request an export review.

This product contains a chemical substance that is subject to a Significant New Use Rule (SNUR) under Section 5(a)(2) of TSCA:

Alkanes, C22-30-branched and linear, chloro 4-Nonylphenol, branched

40 CFR 721.10674 (PMN P-13-0107)
79 FR 59186, Oct 1, 2014 (proposed rule)

FEDERAL REPORTING

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
Dichloromethane	75-09-2	50 - 70
Toluene	108-88-3	1 - 5
Methyl isobutyl ketone	108-10-1	0.1 - 1
Methanol	67-56-1	0.1 - 1

STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List		CAS	Percent
Dichloromethane	(Carcinogen)	75-09-2	50 - 70
Titanium dioxide	(Carcinogen)	13463-67-7	0.1 - 1
Methyl isobutyl ketone	(Carcinogen)	108-10-1	0.1 - 1
Quartz	(Carcinogen)	14808-60-7	0.001 - 0.01
ethylbenzene	(Carcinogen)	100-41-4	0.001 - 0.01
Acetaldehyde	(Carcinogen)	75-07-0	0.001 - 0.01
Toluene	(Developmental toxin)	108-88-3	1 - 5
Methyl isobutyl ketone	(Developmental toxin)	108-10-1	0.1 - 1
Methanol	(Developmental toxin)	67-56-1	0.1 - 1
Benzene, methyl-	(Female reproductive toxin)	108-88-3	1 - 5

Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's at 0.1% or greater, as of the version date of this SDS.

SAFETY DATA SHEET

SECTION 16: OTHER INFORMATION

SDS VERSION DATE: 06-23-2020

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 0 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.