

Foster® CRYOLAR[™] 90-61

Version 1.2

Revision Date 12/16/2022

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	Foster® CRYOLAR™ 90-61
Product code	:	10000015225

Manufacturer or supplier's details

Company	: H.B.	Fuller Company
Address) Willow Lake Boulevard nais Heights, MN 55110
Telephone		8-423-8553

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use	:	Solvent based adhesive
Restrictions on use	:	For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Color	gray
Odor	solvent

GHS Classification

Flammable liquids Skin irritation Eye irritation Skin sensitization Specific target organ toxicity - single exposure	 Category 3 Category 2 Category 2A Category 1 Category 3 (Respiratory system)
Aspiration hazard	: Category 1
GHS label elements	
Hazard pictograms	
Signal Word	: Danger



Foster® CRYOLAR[™] 90-61

Version 1.2

Revision Date 12/16/2022

Hazard Statements:

H226 Flammable liquid and vapor. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

Precautionary Statements:

Prevention: P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ eye protection/ face protection.

Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P331 Do NOT induce vomiting. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

~			
(:ai	rcina	JUGEN	icity:
oui		Jacii	iony.

IARC	Group 1: Carcinogenic to humans product, this substance is enca will not present a cancer expose Quartz (SiO2)	apsulated within the product and
		to humansDuring normal handling is encapsulated within the product exposure risk. 13463-67-7
	cumene	98-82-8
OSHA	No component of this product equal to 0.1% is on OSHA's lis	present at levels greater than or t of regulated carcinogens.
NTP	Known to be human carcinogenD product, this substance is enca will not present a cancer expose Quartz (SiO2)	apsulated within the product and
	Reasonably anticipated to be a hu handling of the product, this su the product and will not presen cumene	bstance is encapsulated within



Foster® CRYOLAR[™] 90-61

Version 1.2

Revision Date 12/16/2022

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
calcium carbonate	471-34-1	20 - 30
1,2,4-trimethylbenzene	95-63-6	10 - 20
Mica	12001-26-2	1 - 5
Stoddard solvent	8052-41-3	1 - 5
mesitylene	108-67-8	1 - 5
titanium dioxide	13463-67-7	1 - 5
Wollastonite (Ca(SiO3))	13983-17-0	1 - 5
cumene	98-82-8	1 - 5
Xylene	1330-20-7	1 - 5
diethylbenzene	25340-17-4	1 - 5
2-(propyloxy)ethanol	2807-30-9	1 - 5
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	1 - 5
Quartz (SiO2)	14808-60-7	1 - 5
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	0.1 - 1
Actual concentration is withheld as a trade secret		

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	Show this material safety data sheet to the doctor in attendance.	
If inhaled	Move to fresh air. If symptoms persist, call a physician.	
In case of skin contact	Wash off with soap and water. Get medical attention if irritation develops and persis	sts.
In case of eye contact	Flush eyes with water at least 15 minutes. Get mediattention if eye irritation develops or persists.	cal
If swallowed	Do NOT induce vomiting. If victim is fully conscious, give a cupful of water. Never give anything by mouth to an unconscious pe Obtain medical attention.	rson.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or
		carbon dioxide.



Foster® CRYOLAR[™] 90-61

sion 1.2	Revision Date 12/16/2022
Specific hazards during fire fighting	: Cool closed containers exposed to fire with water spray.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatu Use personal protective equipment.
TION 6. ACCIDENTAL RELEA	ASE MEASURES
Personal precautions, protective equipment and emergency procedures	ASE MEASURES Remove all sources of ignition. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Refer to protective measures listed in sections 7 and 8.
Personal precautions, protective equipment and	 Remove all sources of ignition. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation	: Use only with adequate ventilation.
Advice on safe handling	 Avoid inhalation of vapor or mist. Do not use in areas without adequate ventilation. Keep away from fire, sparks and heated surfaces. Keep container closed when not in use. Take precautionary measures against static discharges.
Conditions for safe storage	 Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from sources of ignition - No smoking. Solvent vapors are heavier than air and may spread along floors.
Materials to avoid	: Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters



Foster® CRYOLAR[™] 90-61

Version 1.2

Revision Date 12/16/2022

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible	Basis
calcium carbonate	471-34-1	PEL (Total	concentration 10 mg/m3	CAL PEL
calcium carbonate		dust)	10 119/110	OALTEL
		PEL (respirable dust fraction)	5 mg/m3	CAL PEL
Mica	12001-26-2	TWA (Respirable particulate matter)	0.1 mg/m3	ACGIH
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable fraction)	3 mg/m3	OSHA P0
		TWA (Respirable)	3 mg/m3	NIOSH REL
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		С	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
titanium dioxide	13463-67-7	TWA	10 mg/m3	ACGIH
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total)	10 mg/m3	OSHA P0
		TWA (Total dust)	10 mg/m3	OSHA P0
Wollastonite (Ca(SiO3))	13983-17-0	TWA (Inhalable particulate matter)	1 mg/m3	ACGIH
cumene	98-82-8	TWA	5 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0
		PEL	50 ppm 245 mg/m3	CAL PEL
Xylene	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m3	OSHA P0



Foster® CRYOLAR™ 90-61

Version 1.2

Revision Date 12/16/2022

			i.	
		TWA	100 ppm 435 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		STEL	150 ppm 655 mg/m3	CAL PEL
		С	300 ppm	CAL PEL
		PEL	100 ppm 435 mg/m3	CAL PEL
Quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL
		TWÁ (respirable dust fraction)	0.1 mg/m3	OSHA P0

Engineering measures	:	Use local exhaust ventilation or other engineering controls to minimize exposures.
Personal protective equipme	ent	
Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Filter type	:	Organic vapor Type
Hand protection Material	:	Nitrile rubber
Eye protection	:	Safety glasses with side-shields
Hygiene measures	:	Avoid contact with skin, eyes and clothing. Provide adequate ventilation.
		6 / 13



Foster® CRYOLAR[™] 90-61

Version 1.2

Revision Date 12/16/2022

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Color Odor Odor Threshold	-	liquid gray solvent no data available
рН	:	Not applicable
Melting point/freezing point	:	is not determined
Boiling point/boiling range	:	is not determined
Flash point Evaporation rate Upper explosion limit	:	46 °CMethod: Tag closed cup is not determined Upper flammability limit is not determined
Lower explosion limit	:	Lower flammability limit is not determined
Vapor pressure	:	is not determined
Density Solubility(ies)	:	9.1 - 9.5 lb/gal
Water solubility	:	is not determined
Partition coefficient: n- octanol/water	:	no data available
Autoignition temperature	:	is not determined
Viscosity Viscosity, kinematic VOC, less water, in g/l	:	is not determined 484

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Hazardous polymerization does not occur.
Conditions to avoid	: Heat, flames and sparks.
Hazardous decomposition products	: Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity



Foster® CRYOLAR™ 90-61		
Version 1.2	Revision Date 12/16/2022	
Product:		
Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method	
Acute inhalation toxicity	: Acute toxicity estimate : 82.62 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method	
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method	
Components:		
1,2,4-trimethylbenzene:		
Acute oral toxicity	: LD50 Oral Rat: 3,400 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 18 mg/l Exposure time: 4 h Test atmosphere: vapor	
Acute dermal toxicity	: LD50 Dermal Rabbit: > 3,160 mg/kg	
cumene: Acute oral toxicity	: LD50 Oral Rat: 1,400 mg/kg	
Xylene:		
Acute oral toxicity	: LD50 Oral Rat: 4,300 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 47,635 mg/l Exposure time: 4 h Test atmosphere: vapor	
bis(1,2,2,6,6-pentamethyl-4 Acute oral toxicity	-piperidyl) sebacate: : LD50 Oral Rat: 2,615 mg/kg	
Skin corrosion/irritation		
No data available		
Serious eye damage/eye irritatio	วท	
No data available		
Respiratory or skin sensitization	n	
No data available		
Germ cell mutagenicity		
No data available		
	8 / 13	



Foster® CRYOLAR™ 90-61

Version 1.2

Revision Date 12/16/2022

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

<u>Components:</u> 1,2,4-trimethylbenzene :	
Toxicity to fish	 LC50 (Pimephales promelas (fathead minnow)): 7.19 - 8.28 mg/l Exposure time: 96 h Test Method: flow-through test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 6.14 mg/l Exposure time: 48 h Test Method: static test
mesitylene :	
Toxicity to fish	 LC50 (Pimephales promelas (fathead minnow)): 3.48 mg/l Exposure time: 96 h Test Method: static test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 50 mg/l Exposure time: 24 h Test Method: static test
cumene :	
Toxicity to fish	 LC50 (Oncorhynchus mykiss (rainbow trout)): 2.7 mg/l Exposure time: 96 h Test Method: semi-static test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 0.6 mg/l Exposure time: 48 h Test Method: static test
	9 / 13



Foster® CRYOLAR[™] 90-61

Version 1.2	Revision Date 12/16/2022
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (microalgae)): 2.6 mg/l Exposure time: 72 h Test Type: flow-through test
bis(1,2,2,6,6-pentamethyl-	-4-piperidyl) sebacate :
Toxicity to fish	 LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.97 mg/l Exposure time: 96 h Test Method: static test
Persistence and degradability	
No data available Bioaccumulative potential	
Mobility in soil	
No data available	
Other adverse effects	
No data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	 This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements. The hazard and precautionary statements displayed on the label also apply to any residues left in the container.
	abor also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR	
UN/ID No.	: UN 1993
Proper shipping name	: Flammable liquid, n.o.s. (PETROLEUM DISTILLATES)
Class	: 3
Packing group	: 111
Labels	: Flammable Liquids
IMDG-Code	
UN number	: UN 1993
Proper shipping name	: FLAMMABLE LIQUID, N.O.S.
1 11 0	(PETROLEUM DISTILLATES)
Class	: 3
	10 / 13



Foster® CRYOLAR[™] 90-61

Version 1.2

Revision Date 12/16/2022

Packing group	:	III
Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
Marine pollutant	:	yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR		
UN/ID/NA number	:	UN 1993
Proper shipping name	:	Flammable liquids, n.o.s. (PETROLEUM DISTILLATES)
Class	:	3
Packing group	:	III
Labels	:	FLAMMABLE LIQUID
ERG Code	:	128
Marine pollutant	:	yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards	Flammable (gases, aerosols, liquids, or solids) Respiratory or skin sensitization Aspiration hazard Skin corrosion or irritation Serious eye damage or eye irritation Specific target organ toxicity (single or repeated exposure)		
SARA 302	This material does not contain any components with a section 302 EHS TPQ.		
SARA 313	: The following components are subject to rep by SARA Title III, Section 313:	owing components are subject to reporting levels established A Title III, Section 313:	
	1,2,4-trimethylbenzene	95-63-6	
	cumene	98-82-8	
	Xylene	1330-20-7	
	2-(propyloxy)ethanol	2807-30-9	

Clean Air Act



Foster® CRYOLAR™ 90-61

Version 1.2

Revision Date 12/16/2022


The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

0.1).	cumene Xylene		98-82-8 1330-20-7	
	2-(propyloxy)ethanol		2807-30-9	
US State Regulations				
Californi	ia Prop 65	Please contact Supplier for more information.		
The ingredients of this product are reported in the following inventories:TSCAAll substances listed as active on the TSCA inventory				
DSL		All components of this product are on the Canadian DSL		
AIIC		On the inventory, or in compliance with the inventory		
ENCS		On the inventory, or in compliance with the inventory		
KECI		On the inventory, or in compliance with the inventory		
PICCS		On the inventory, or in compliance	with the inventory	
IECSC On the inventory, or in compliance with the inventory Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)				

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com





The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.