

Print Date: 01-09-2017 FOSTER 10-42 802237PM

SAFETY DATA SHEET

REVISION DATE: 03-25-2015 SUPERSEDES: 09-29-2014

SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER

PRODUCT INFORMATION

PRODUCT: FOSTER 10-42

PRODUCT DESCRIPTION: Sealant INTENDED USE: Sealant PRODUCT IDENTIFIER: 802237PM

COMPANY INFORMATION

H.B. Fuller Construction Products Inc.

1105 S. Frontenac Street Aurora, IL 60504

Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

GHS Hazard Symbols:



GHS Signal Word: Warning

GHS Classification: Flammable Liquid Category 3; Hazardous to the aquatic environment - Acute

Category 3; Hazardous to the aquatic environment - Chronic Category 3

GHS Hazard Phrases: Flammable liquid and vapour.; Harmful to aquatic life.; Harmful to aquatic life with

long lasting effects.

GHS Precautions:

Safety Precautions: Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container

tightly closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

skin with water/shower. In case of fire: Use water spray, foam, dry chemical or carbon

dioxide to extinguish.

Storage: Keep container tightly closed. Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local/regional/national/international

regulation for hazardous wastes.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	PERCENT	Classification	Note
Polybutene	9003-29-6	10 - 30	Aquatic Chronic 4; H413	
Stoddard solvent	8052-41-3	5 - 10	Asp. Tox. 1; H304	Note P



FOSTER 10-42 Print Date: 01-09-2017 802237PM

SAFETY DATA SHEET

Fuller's earth	8031-18-3	5 - 10	Aquatic Chronic 2; H411 Acute Tox. 4; H302	* (see below)
Trimethylbenzene, 1,2,4-	95-63-6	1 - 5	Aquatic Chronic 2; H411 Acute Tox. 4; H332 Eye Irrit. 2; H319 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT SE 3; H335	
Crystalline silica	14808-60-7	0.1 - 1	Carc. 1A; H350 STOT RE 1; H372	* (see below)

^{*}This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

IF IN EYES: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention immediately. Drink two glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

Use water spray, foam, dry chemical or carbon dioxide. **EXTINGUISHING MEDIA:**

Vapors are heavier than air and can travel to a source of ignition UNUSUAL FIRE AND EXPLOSION HAZARDS:

and flash back.

SPECIAL FIRE FIGHTING INSTRUCTIONS: Persons exposed to products of combustion should wear self-

contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: Exposure to the spilled material may be irritating or harmful. Follow

personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Evaporation of volatile substances can lead to the displacement of air creating an

environment that can cause asphyxiation.

METHODS FOR CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to

containers for disposal. Keep spilled product out of sewers, watersheds,

or water systems.

Shut off ignition sources; including electrical equipment and flames. Do

not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300



FOSTER 10-42 802237PM

SAFETY DATA SHEET

SECTION 7: HANDLING AND STORAGE

Handling: Avoid contacting and avoid breathing the material. Use only in a well ventilated

area.

Keep away from heat, sparks and flame.

Wash thoroughly after handling.

Keep container closed.

Emptied container retains vapor and product residue.

Observe all labeled precautions until container is cleaned.

Drums of this material should be grounded when pouring.

DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.

Storage: Store in a cool, dry, ventilated location. Keep away from heat and flame. Keep

container closed.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS:

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Calcium carbonate	* (see below)	No data available.	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
Stoddard solvent	Note P	100 ppm TWA	500 ppm TWA; 2900 mg/m3 TWA
Mineral oil	Note L	No data available.	5 mg/m3 TWA (as mist)
Crystalline silica	* (see below)	0.025 mg/m3 TWA (respirable fraction)	((250)/(%SiO2 + 5) mppcf TWA (respirable)); ((10)/(%SiO2 + 2) mg/m3 TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust))
Cumene		50 ppm TWA	50 ppm TWA; 245 mg/m3 TWA Skin absorption may potentially contribute to the overall exposure to this material.
Xylene		100 ppm TWA 150 ppm STEL	100 ppm TWA; 435 mg/m3 TWA

^{*}This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

ENGINEERING CONTROL METHODS:

VENTILATION: Use local exhaust ventilation or other engineering controls to

minimize exposures.

EYE PROTECTION: Wear safety glasses with side shields when handling this product.

Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash

station available.

SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves. Skin

absorption may potentially contribute to the overall exposure to this

material. Appropriate measures should be taken to prevent



Print Date: 01-09-2017 FOSTER 10-42 802237PM

SAFETY DATA SHEET

absorption so that the TLV is not invalidated.

GLOVES: Nitrile

RESPIRATORY PROTECTION: Respiratory protection may be required to avoid overexposure when

handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved

air purifying respirator with organic vapor cartridge.

Respirators should be selected by and used following requirements

found in OSHA's respirator standard (29 CFR 1910.134).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid COLOR: Off-white Solvent ODOR: ODOR THRESHOLD: Not established Not established FREEZING/MELTING POINT (deg. C): Not established BOILING POINT (deg. C): Not established 46°C; 115°F TCC FLASH POINT: **EVAPORATION RATE:** Not established

FLAMMABILITY: Not a flammable solid or gas

UPPER EXPLOSIVE LIMIT (% in air):

LOWER EXPLOSIVE LIMIT (% in air):

VAPOR PRESSURE (mm Hg):

VAPOR DENSITY:

Not established

Not established

WEIGHT PER GALLON (lbs.): 11.04 SPECIFIC GRAVITY: 1.320

SOLUBILITY:

OCTANOL/WATER COEFFICIENT:

AUTOIGNITION TEMPERATURE:

DECOMPOSITION TEMPERATURE:

VISCOSITY:

Not established

Not established

Not established

Not established

SOLIDS (% by weight): 87.9 VOC, weight percent 13.08

VOC, U.S. EPA Method 24, less water and exempt 172.7g/liter of material

solvents (theoretically determined)

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions. CHEMICAL INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide

SECTION 11: TOXICOLOGICAL INFORMATION

Component Toxicity / Toxicology Data:

COMPONENT NAME	LD50/LC50
Calcium carbonate	ORAL LD50 RAT 6,450 MG/KG
Trimethylbenzene, 1,2,4-	ORAL LD50 RAT 3,400 MG/KG
•	INHALATION LC50-4H RAT 18.00 G/M3
	DERMAL LD50 RABBIT > 3,160.00 MG/KG



FOSTER 10-42 802237PM

SAFETY DATA SHEET

This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: Can cause skin irritation.

Serious eye damage / irritation :Can cause moderate irritation, tearing and reddening.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: Contains a substance that is a probable reproductive hazard based on human studies.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: May cause respiratory irritation.

Specific target organ toxicity-repeated exposure: No data available.

Target organs potentially affected by exposure: Kidneys Central nervous system Lungs Blood Liver

Aspiration hazard: No data available.

Medical Conditions Aggravated by Exposure: Kidney disease, Lung disease, Blood disorders (like anemia), Liver disease

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available for this product.

MOBILITY: No data available.
PERSISTENCE: No data available.
BIOACCUMULATION: No data available.

This product has not been tested for ecological effects. Relevant information for components is listed below:

Component:	Ecotoxicity values:
Mineral oil	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
	Acute Toxicity (Daphnia): 48 Hr EC50 Daphnia magna: >1000 mg/L
	Acute Toxicity (Algae): Not established
Trimethylbenzene, 1,2,4-	Acute Toxicity (Fish): 96 Hr LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-
	through]
	Acute Toxicity (Daphnia): 48 Hr EC50 Daphnia magna: 6.14 mg/L
	Acute Toxicity (Algae): Not established

SECTION 13: DISPOSAL CONSIDERATIONS

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

LAND DISPOSAL RESTRICTIONS: Xylenes (o-, m-, p- isomers)

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

US DOT: UN1133, ADHESIVES, 3, III IATA: UN1133, ADHESIVES, 3 III IMDG: UN1133, ADHESIVES, 3, III



FOSTER 10-42 802237PM

SAFETY DATA SHEET

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's

Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt

from DSL requirements.

EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product

cannot be imported into Europe unless the REACH requirements are

met.

AUSTRALIA AICS: This product is in compliance with the Australian Inventory of

Chemical Substances requirements.

KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List

requirements.

PHILIPPINES: This product is in compliance with the Philippine Inventory of

Chemicals and Chemical Substances requirements.

CHINA IECSC INVENTORY: This product is in compliance with the Inventory of Existing Chemical

Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg,request@hbfuller.com to request an export review.

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
1,2,4-Trimethylbenzene	95-63-6	1 - 5
Cumene	98-82-8	0.1 - 1
Xylene (mixed isomers)	1330-20-7	0.1 - 1

STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List		CAS	Percent
Quartz	(Carcinogen)	14808-60-7	0.1 - 1
Cumene	(Carcinogen)	98-82-8	0.1 - 1
Naphthalene	(Carcinogen)	91-20-3	0.01 - 0.1
ethylbenzene	(Carcinogen)	100-41-4	0.01 - 0.1
Benzene	(Carcinogen)	71-43-2	< 10 ppm
Benzene	(Developmental toxin)	71-43-2	< 10 ppm
Methyl chloride	(Developmental toxin)	74-87-3	< 10 ppm
Toluene	(Developmental toxin)	108-88-3	< 10 ppm
Benzene, methyl-	(Female reproductive toxin)	108-88-3	< 10 ppm
Benzene	(Male reproductive toxin)	71-43-2	< 10 ppm
Chloromethane	(Male reproductive toxin)	74-87-3	< 10 ppm

Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's.



FOSTER 10-42 802237PM

SAFETY DATA SHEET

SECTION 16: OTHER INFORMATION

SDS VERSION DATE: 03-25-2015

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 2 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B.Fuller Construction Products, Inc. from its suppliers, and because H.B.Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B.Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B.Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B.Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.