

FOSTER 85-15
Print Date: 01-09-2017 802413PM

SAFETY DATA SHEET

REVISION DATE: 03-26-2015 SUPERSEDES: 03-20-2015

SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER

PRODUCT INFORMATION

PRODUCT: FOSTER 85-15
PRODUCT DESCRIPTION: Adhesive
INTENDED USE: Adhesive
PRODUCT IDENTIFIER: 802413PM

COMPANY INFORMATION

H.B. Fuller Construction Products Inc. 1105 S. Frontenac Street

Aurora, IL 60504

Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

GHS Hazard Symbols:









GHS Signal Word: Danger

GHS Flammable Liquid Category 1; Skin Sensitisation Category 1; Skin Corrosion/Irritation

Classification: Category 2; Reproductive Toxicity Category 2; Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2; Hazardous to the aquatic environment - Acute

Category 2; Hazardous to the aquatic environment - Chronic Category 2; Specific Target

Organ Systemic Toxicity (STOT) - Single Exposure Category 3

GHS Hazard Extremely flammable liquid and vapour.; Causes skin irritation.; May cause an allergic skin reaction.; May cause drowsiness or dizziness.; Suspected of damaging fertility or the

reaction.; May cause drowsiness or dizziness.; Suspected of damaging fertility or the unborn child.; May cause damage to organs through prolonged or repeated exposure.; Toxic

to aquatic life.; Toxic to aquatic life with long lasting effects.

GHS Precautions:

Safety Precautions: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe

dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective

clothing/eye protection/face protection.

First Aid Measures: IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation or rash occurs: Get medical



Print Date: 01-09-2017 FOSTER 85-15 802413PM

SAFETY DATA SHEET

advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use

water spray, foam, dry chemical or carbon dioxide to extinguish. Collect spillage.

Storage: Keep container tightly closed. Store in a well-ventilated place. Keep container tightly

closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container in accordance with local/regional/national/international

regulation for hazardous wastes.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	PERCENT	Classification	Note
Hexane, n	110-54-3	30 - 50	Aquatic Chronic 2; H411	
			Asp. Tox. 1; H304	
			Flam. Liq. 2; H225	
			Repr. 2; H361	
			Skin Irrit. 2; H315	
			STOT RE 2; H373	
			STOT SE 3; H336	
Toluene	108-88-3	10 - 30	Asp. Tox. 1; H304	
			Acute Tox. 4; H302	
			Flam. Liq. 2; H225	
			Repr. 2; H361	
			Skin Irrit. 2; H315	
			STOT RE 2; H373	
			STOT SE 3; H336	
Tri(nonylphenol)phosphite	26523-78-4	0.1 - 1	Aquatic Acute 1; H400	
			Aquatic Chronic 1; H410	
			Skin Sens. 1; H317	

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

IF IN EYES: Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention immediately. Drink two glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water spray, foam, dry chemical or carbon dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and can travel to a source of ignition

and flash back.

SPECIAL FIRE FIGHTING INSTRUCTIONS: Persons exposed to products of combustion should wear self-

contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide



FOSTER 85-15 802413PM

SAFETY DATA SHEET

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: Exposure to the spilled material may be irritating or harmful. Follow

> personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Evaporation of volatile substances can lead to the displacement of air creating an

environment that can cause asphyxiation.

METHODS FOR CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to

containers for disposal. Keep spilled product out of sewers, watersheds,

or water systems.

Shut off ignition sources; including electrical equipment and flames. Do

not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: Avoid contacting and avoid breathing the material. Use only in a well ventilated

area.

Keep away from heat, sparks and flame.

Wash thoroughly after handling.

Keep container closed.

Emptied container retains vapor and product residue. Observe all labeled precautions until container is cleaned. Drums of this material should be grounded when pouring. DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.

Storage: Store in a cool, dry, ventilated location. Keep away from heat, sparks, flame and

other sources of ignition. Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS:

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Hexane, n		50 ppm TWA Skin absorption may potentially contribute to the overall exposure to this material.	500 ppm TWA; 1800 mg/m3 TWA
Toluene		20 ppm TWA	200 ppm TWA 300 ppm Ceiling

ENGINEERING CONTROL METHODS:

VENTILATION: Use local exhaust ventilation or other engineering controls to

minimize exposures.

EYE PROTECTION: Wear safety glasses with side shields when handling this product.

> Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash

station available.



FOSTER 85-15
Print Date: 01-09-2017 802413PM

SAFETY DATA SHEET

SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves and long

sleeved shirt. An apron may be appropriate if splashing can occur. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent

absorption so that the TLV is not invalidated.

GLOVES: Nitrile

RESPIRATORY PROTECTION: Respiratory protection may be required to avoid overexposure when

handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved

air purifying respirator with organic vapor cartridge.

Respirators should be selected by and used following requirements

found in OSHA's respirator standard (29 CFR 1910.134).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid COLOR: Yellow ODOR: Solvent

ODOR THRESHOLD:

PH:

Not established

FLASH POINT:

-18°C; 0°F TCC

EVAPORATION RATE:

Not established

FLAMMABILITY: Not a flammable solid or gas

UPPER EXPLOSIVE LIMIT (% in air):

LOWER EXPLOSIVE LIMIT (% in air):

VAPOR PRESSURE (mm Hg):

Not established

VAPOR DENSITY:

Not established

WEIGHT PER GALLON (lbs.): 6.60 SPECIFIC GRAVITY: 0.790

SOLUBILITY: Not established OCTANOL/WATER COEFFICIENT: Not established AUTOIGNITION TEMPERATURE: Not established DECOMPOSITION TEMPERATURE: Not established VISCOSITY: No data available.

SOLIDS (% by weight): 38.6 VOC, weight percent 61.70

VOC, U.S. EPA Method 24, less water and exempt 487g/liter of material

solvents (theoretically determined)

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions. CHEMICAL INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide

SECTION 11: TOXICOLOGICAL INFORMATION

Component Toxicity / Toxicology Data:

COMPO	NENT NAME	LD50/LC50



FOSTER 85-15 802413PM

SAFETY DATA SHEET

Hexane, n	INHALATION LC50-4H RAT 48,000.00 PPM	
	DERMAL LD50 RABBIT 3,000.00 MG/KG	
Toluene	ORAL LD50 RAT 636 MG/KG	
	INHALATION LC50-4H RAT 12.50 MG/L	
	DERMAL LD50 RABBIT 8,390.00 MG/KG	

This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Serious eye damage / irritation :Eye contact may cause moderate to severe eye irritation. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: No data available.

Carcinogenicity: No data available.

Reproductive toxicity: Contains a substance that is a possible reproductive hazard based on animal studies.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: May cause drowsiness or dizziness.

Specific target organ toxicity-repeated exposure: May cause damage to organs through prolonged or repeated exposure.

Target organs potentially affected by exposure: Central nervous system Peripheral nervous system Reproductive system Liver

Aspiration hazard: No data available.

Medical Conditions Aggravated by Exposure: Liver disease

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available for this product.

MOBILITY: No data available.
PERSISTENCE: No data available.
BIOACCUMULATION: No data available.

This product has not been tested for ecological effects. Relevant information for components is listed below:

Component:	Ecotoxicity values:
Hexane, n	Acute Toxicity (Fish): 96 Hr LC50 Pimephales promelas: 2.1 - 2.98 mg/L [flow-
	through]
	Acute Toxicity (Daphnia): Not established
	Acute Toxicity (Algae): Not established
Toluene	Acute Toxicity (Fish): 96 Hr LC50 Pimephales promelas: 15.22 - 19.05 mg/L [flow-
	through] (1 day old); 96 Hr LC50 Pimephales promelas: 12.6 mg/L [static]; 96 Hr LC50
	Oncorhynchus mykiss: 5.89 - 7.81 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus
	mykiss: 14.1 - 17.16 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 5.8 mg/L [semi-
	static]; 96 Hr LC50 Lepomis macrochirus: 11.0 - 15.0 mg/L [static]; 96 Hr LC50 Oryzias
	latipes: 54 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 28.2 mg/L [semi-static]; 96 Hr
	LC50 Poecilia reticulata: 50.87 - 70.34 mg/L [static]
	Acute Toxicity (Daphnia): 48 Hr EC50 Daphnia magna: 5.46 - 9.83 mg/L [Static]; 48
	Hr EC50 Daphnia magna: 11.5 mg/L
	Acute Toxicity (Algae): 96 Hr EC50 Pseudokirchneriella subcapitata: >433 mg/L; 72 Hr
	EC50 Pseudokirchneriella subcapitata: 12.5 mg/L [static]



FOSTER 85-15 802413PM

SAFETY DATA SHEET

SECTION 13: DISPOSAL CONSIDERATIONS

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

LAND DISPOSAL RESTRICTIONS: Toluene

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

US DOT: UN1133, ADHESIVES, 3, II, MARINE POLLUTANT (HEXANE)
IATA: UN1133, ADHESIVES, 3, II, MARINE POLLUTANT (HEXANE)
IMDG: UN1133, ADHESIVES, 3, II, MARINE POLLUTANT (HEXANE)

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's

Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt

from DSL requirements.

EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product

cannot be imported into Europe unless the REACH requirements are

met.

AUSTRALIA AICS: This product is in compliance with the Australian Inventory of

Chemical Substances requirements.

KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List

requirements.

PHILIPPINES: This product is in compliance with the Philippine Inventory of

Chemicals and Chemical Substances requirements.

CHINA IECSC INVENTORY: This product is in compliance with the Inventory of Existing Chemical

Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg.request@hbfuller.com to request an export review.

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
n-Hexane	110-54-3	30 - 50
Toluene	108-88-3	10 - 30

STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.



FOSTER 85-15 802413PM

SAFETY DATA SHEET

Chemical Name/List		CAS	Percent
Benzene	(Carcinogen)	71-43-2	0.001 - 0.01
Toluene	(Developmental toxin)	108-88-3	10 - 30
Benzene	(Developmental toxin)	71-43-2	0.001 - 0.01
Benzene, methyl-	(Female reproductive toxin)	108-88-3	10 - 30
Benzene	(Male reproductive toxin)	71-43-2	0.001 - 0.01

Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's.

SECTION 16: OTHER INFORMATION

SDS VERSION DATE: 03-26-2015

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 3 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B.Fuller Construction Products, Inc. from its suppliers, and because H.B.Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B.Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B.Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B.Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.