

CHILDERS CP-129 815317PM

SAFETY DATA SHEET

REVISION DATE: 02-04-2020 **SUPERSEDES:** 06-21-2017

SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER

PRODUCT INFORMATION

PRODUCT: **CHILDERS CP-129**

PRODUCT DESCRIPTION: Adhesive INTENDED USE: Adhesive PRODUCT IDENTIFIER: 815317PM

COMPANY INFORMATION

H.B. Fuller Construction Products Inc.

1105 S. Frontenac Street Aurora, IL 60504

Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

GHS Hazard Symbols:









GHS Signal Word: Danger

GHS

Skin Sensitisation Category 1; Carcinogenicity Category 1B; Flammable Liquid Category 2; Skin Corrosion/Irritation Category 2; Reproductive Toxicity Category 2; Specific Target Classification:

Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2; Hazardous to the aquatic environment - Chronic Category 2; Specific Target Organ Systemic Toxicity

(STOT) - Single Exposure Category 3

GHS Hazard Highly flammable liquid and vapour.; Causes skin irritation.; May cause an allergic skin Phrases: reaction.; May cause respiratory irritation.; May cause drowsiness or dizziness.; May cause

cancer.; Suspected of damaging fertility or the unborn child.; May cause damage to organs through prolonged or repeated exposure.; Toxic to aquatic life with long lasting effects.

GHS Precautions:

Safety **Precautions:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe

dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective

clothing/eye protection/face protection.

First Aid Measures: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. P362+P364 - Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. In case of fire: Use water spray, foam, dry chemical or carbon dioxide to extinguish.



CHILDERS CP-129 815317PM

SAFETY DATA SHEET

Collect spillage.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated

place. Keep cool. Store locked up.

Disposal: Dispose of contents/container in accordance with local/regional/national/international

regulation for chemical wastes.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS# | PERCENT | Classification | Note |
|---------------------------------------|------------|---------|-------------------------|------|
| Hexane, n | 110-54-3 | 50 - 70 | Aquatic Chronic 2; H411 | |
| | | | Asp. Tox. 1; H304 | |
| | | | Flam. Liq. 2; H225 | |
| | | | Repr. 2; H361 | |
| | | | Skin Irrit. 2; H315 | |
| | | | STOT RE 2; H373 | |
| | | | STOT SE 3; H335, H336 | |
| Toluene | 108-88-3 | 1 - 5 | Asp. Tox. 1; H304 | |
| | | | Flam. Liq. 2; H225 | |
| | | | Repr. 2; H361 | |
| | | | Skin Irrit. 2; H315 | |
| | | | STOT RE 2; H373 | |
| | | | STOT SE 3; H335, H336 | |
| Extracts, petroleum, heavy paraffinic | 64742-04-7 | 0.1 - 1 | Carc. 1B; H350 | |
| distillate | | | | |
| Tri(nonylphenol)phosphite | 26523-78-4 | 0.1 - 1 | Aquatic Chronic 1; H410 | |
| | | | Skin Sens. 1; H317 | |

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

IF IN EYES: None expected to be needed, however, use an eye wash to remove a chemical from your eye regardless of the level of hazard.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist. IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water spray, foam, dry chemical or carbon dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and can travel to a source of ignition

and flash back.

SPECIAL FIRE FIGHTING INSTRUCTIONS: Persons exposed to products of combustion should wear self-

contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide

SECTION 6: ACCIDENTAL RELEASE MEASURES



CHILDERS CP-129 815317PM

SAFETY DATA SHEET

SPECIAL PROTECTION: Exposure to the spilled material may be irritating or harmful. Follow

personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Evaporation of volatile substances can lead to the displacement of air creating an

environment that can cause asphyxiation.

METHODS FOR CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to

containers for disposal. Keep spilled product out of sewers, watersheds,

or water systems.

Shut off ignition sources; including electrical equipment and flames. Do

not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: Avoid contacting and avoid breathing the material. Use only in a well ventilated

area.

Keep away from heat, sparks and flame.

Wash thoroughly after handling.

Keep container closed.

Emptied container retains vapor and product residue.

Observe all labeled precautions until container is cleaned.

Drums of this material should be grounded when pouring.

DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.

Storage: Store in a cool, dry, ventilated location. Keep away from heat, sparks, flame and

other sources of ignition. Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS:

| Chemical Name | Note | ACGIH EXPOSURE LIMITS | OSHA PEL |
|---------------|------|---|--------------------------------|
| Hexane, n | | 50 ppm TWA Skin absorption may potentially contribute to the overall exposure to this material. | 500 ppm TWA; 1800 mg/m3 TWA |
| Γoluene | | 20 ppm TWA | 200 ppm TWA 300 ppm Ceiling |

ENGINEERING CONTROL METHODS:

VENTILATION: Use local exhaust ventilation or other engineering controls to

minimize exposures.

EYE PROTECTION: Wear safety glasses when handling this product.

SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves and long

sleeved shirt. An apron may be appropriate if splashing can occur. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent

absorption so that the TLV is not invalidated.

GLOVES: Nitrile

RESPIRATORY PROTECTION: Respiratory protection may be required to avoid overexposure when



EVAPORATION RATE:

CHILDERS CP-129 815317PM

SAFETY DATA SHEET

handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with organic vapor cartridge.

Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

Not established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid
COLOR: Clear Amber
ODOR: Solvent

ODOR THRESHOLD:

PH:

Not established

FLASH POINT:

-7°C; 19°F TCC

FLAMMABILITY: Not a flammable solid or gas

UPPER EXPLOSIVE LIMIT (% in air):

LOWER EXPLOSIVE LIMIT (% in air):

VAPOR PRESSURE (mm Hg):

VAPOR DENSITY:

Not established

Not established

WEIGHT PER GALLON (lbs.): 6.40 SPECIFIC GRAVITY: 0.730

SOLUBILITY: Not established OCTANOL/WATER COEFFICIENT: Not established AUTOIGNITION TEMPERATURE: Not established DECOMPOSITION TEMPERATURE: Not established VISCOSITY: No data available.

SOLIDS (% by weight): 28.2 VOC, weight percent 66.80

VOC, U.S. EPA Method 24, less water and exempt 512g/liter of material

solvents (theoretically determined)

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.

CHEMICAL INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide

SECTION 11: TOXICOLOGICAL INFORMATION

Component Toxicity / Toxicology Data:

| COMPONENT NAME | LD50/LC50 |
|----------------|-----------------------------------|
| Hexane, n | Dermal LD50 Rabbit 3,000.00 mg/kg |
| Toluene | Oral LD50 Rat 636 mg/kg |
| | Inhalation LC50 Rat 12.50 mg/l |
| | |

This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.



CHILDERS CP-129 815317PM

SAFETY DATA SHEET

Serious eye damage / irritation :No irritation hazard in normal industrial use.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: Contains a substance that is a possible reproductive hazard based on animal studies.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: No data available.

Specific target organ toxicity-repeated exposure: May cause damage to organs through prolonged or repeated exposure.

Target organs potentially affected by exposure: Central nervous system Peripheral nervous system Reproductive system Liver

Aspiration hazard: Not an aspiration hazard.

Medical Conditions Aggravated by Exposure: Liver disease

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available for this product.

MOBILITY: No data available.
PERSISTENCE: No data available.
BIOACCUMULATION: No data available.

This product has not been tested for ecological effects. Relevant information for components is listed below:

| Component: | Ecotoxicity values: |
|------------|--|
| Hexane, n | Acute Toxicity (Fish): LC50 96 h Pimephales promelas 2.1 - 2.98 mg/L [flow-through] |
| | (EPA) |
| | Acute Toxicity (Daphnia): Not established |
| | Acute Toxicity (Algae): Not established |
| Toluene | Acute Toxicity (Fish): LC50 96 h Pimephales promelas 15.22 - 19.05 mg/L [flow- |
| | through] (1 day old, EPA); LC50 96 h Pimephales promelas 12.6 mg/L [static] (EPA); |
| | LC50 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L [flow-through] (EPA); LC50 96 h |
| | Oncorhynchus mykiss 14.1 - 17.16 mg/L [static] (EPA); LC50 96 h Oncorhynchus |
| | mykiss 5.8 mg/L [semi-static] (EPA); LC50 96 h Lepomis macrochirus 11.0 - 15.0 mg/L |
| | [static] (EPA); LC50 96 h Oryzias latipes 54 mg/L [static] (EPA); LC50 96 h Poecilia |
| | reticulata 28.2 mg/L [semi-static] (EPA); LC50 96 h Poecilia reticulata 50.87 - 70.34 |
| | mg/L [static] (EPA) |
| | Acute Toxicity (Daphnia): EC50 48 h Daphnia magna 5.46 - 9.83 mg/L [Static] (EPA); |
| | EC50 48 h Daphnia magna 11.5 mg/L (IUCLID) |
| | Acute Toxicity (Algae): 72 Hr EC50 Pseudokirchneriella subcapitata: 12.5 mg/L [static] |

SECTION 13: DISPOSAL CONSIDERATIONS

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

LAND DISPOSAL RESTRICTIONS: Toluene

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

US DOT: UN1133, ADHESIVES, 3, II, MARINE POLLUTANT (HEXANE)
IATA: UN1133, ADHESIVES, 3, II, MARINE POLLUTANT (HEXANE)
IMDG: UN1133, ADHESIVES, 3, II, MARINE POLLUTANT (HEXANE),

CHILDERS CP-129 815317PM

SAFETY DATA SHEET

FLASH POINT -6°C C.C., EMS F-E, S-E

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's

Inventory requirements.

CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt

from DSL requirements.

EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product

cannot be imported into Europe unless the REACH requirements are

met.

AUSTRALIA AICS: This product is in compliance with the Australian Inventory of

Chemical Substances requirements.

JAPAN ENCS: This product is in compliance with the Japanese Existing and New

Chemical Substances requirements.

KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List

requirements.

PHILIPPINES: This product is in compliance with the Philippine Inventory of

Chemicals and Chemical Substances requirements.

CHINA IECSC INVENTORY: This product is in compliance with the Inventory of Existing Chemical

Substances in China (IECSC) requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg.request@hbfuller.com to request an export review.

This product contains a chemical substance that is

subject to a Significant New Use Rule (SNUR)

al substance that is 4-Nonylphenol, branched

under Section 5(a)(2) of TSCA: 79 FR 59186, Oct 1, 2014 (proposed rule)

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

| Chemical Name | CAS# | % |
|---------------|----------|---------|
| n-Hexane | 110-54-3 | 50 - 70 |
| Toluene | 108-88-3 | 1 - 5 |

STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

| Chemical Name/List | | CAS | Percent |
|--------------------|-----------------------|----------|--------------|
| Styrene | (Carcinogen) | 100-42-5 | 0.1 - 1 |
| Benzene | (Carcinogen) | 71-43-2 | 0.001 - 0.01 |
| 1,3-Butadiene | (Carcinogen) | 106-99-0 | < 10 ppm |
| Toluene | (Developmental toxin) | 108-88-3 | 1 - 5 |
| Benzene | (Developmental toxin) | 71-43-2 | 0.001 - 0.01 |
| 1,3-Butadiene | (Developmental toxin) | 106-99-0 | < 10 ppm |



CHILDERS CP-129 815317PM

SAFETY DATA SHEET

| Benzene, methyl- | (Female reproductive toxin) | 108-88-3 | 1 - 5 |
|------------------|-----------------------------|----------|--------------|
| 1,3-Butadiene | (Female reproductive toxin) | 106-99-0 | < 10 ppm |
| n-Hexane | (Male reproductive toxin) | 110-54-3 | 50 - 70 |
| Benzene | (Male reproductive toxin) | 71-43-2 | 0.001 - 0.01 |
| 1,3-Butadiene | (Male reproductive toxin) | 106-99-0 | < 10 ppm |

Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's at 0.1% or greater, as of the version date of this SDS.

SECTION 16: OTHER INFORMATION

SDS VERSION DATE: 02-04-2020

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 3 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment

recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.