

SAFETY DATA SHEET**Foster® AIR-TIGHT™ FDS-181 BLACK**

Version 1.1

Revision Date 03/28/2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Foster® AIR-TIGHT™ FDS-181 BLACK
Product code : 100000013725

Manufacturer or supplier's details

Company : H.B. Fuller Construction Products

Address : 1105 South Frontenac
Aurora, IL, 60504

Telephone : 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Water based sealant

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance	liquid
Color	black
Odor	ammoniacal

GHS Classification

Effects on or via lactation :

GHS label elements**Hazard Statements:**

H362 May cause harm to breast-fed children.

Precautionary Statements:

Prevention: P201 Obtain special instructions before use. P263 Avoid contact during pregnancy/ while nursing. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product.

Response: P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Potential Health Effects**Carcinogenicity:**

SAFETY DATA SHEET
Foster® AIR-TIGHT™ FDS-181 BLACK

Version 1.1

Revision Date 03/28/2024

IARC	Group 1: Carcinogenic to humans Quartz (SiO ₂) 14808-60-7 Group 2B: Possibly carcinogenic to humans Paraffin waxes and Hydrocarbon waxes, chloro 63449-39-8 Alkanes, chloro 61788-76-9 Carbon black 1333-86-4
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. Known to be human carcinogen Quartz (SiO ₂) 14808-60-7 Reasonably anticipated to be a human carcinogen Paraffin waxes and Hydrocarbon waxes, chloro 63449-39-8
NTP	

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
Limestone	1317-65-3	30 - 50
aluminium hydroxide	21645-51-2	5 - 10
Paraffin waxes and Hydrocarbon waxes, chloro	63449-39-8	5 - 10
Alkanes, chloro	61788-76-9	5 - 10
Alkanes, C14-17, chloro	85535-85-9	5 - 10
Carbon black	1333-86-4	0.1 - 1
Quartz (SiO ₂)	14808-60-7	0.1 - 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	: Show this material safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. If symptoms persist, call a physician.
In case of skin contact	: Wash off with soap and water.

SAFETY DATA SHEET**Foster® AIR-TIGHT™ FDS-181 BLACK**

Version 1.1

Revision Date 03/28/2024

In case of eye contact	: Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
If swallowed	: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.
Most important symptoms and effects, both acute and delayed	: May cause harm to breast-fed children.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Not combustible. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	: none
Specific hazards during fire fighting	: Cool closed containers exposed to fire with water spray.
Specific extinguishing methods	:
Further information	: This product is an aqueous mixture that will not burn. Dried product film will burn in a fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Refer to protective measures listed in sections 7 and 8.
Environmental precautions	: No special environmental precautions required. Prevent product from entering drains.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: No special precautions are needed in handling this material.
Conditions for safe storage	: Keep container closed when not in use. Keep in a dry, cool place.
Materials to avoid	: Do not freeze. No special restrictions on storage with other products.

SAFETY DATA SHEET
Foster® AIR-TIGHT™ FDS-181 BLACK

Version 1.1

Revision Date 03/28/2024

 Storage temperature : ≥ 40 °F

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	TWA (Respirable)	5 mg/m ³	NIOSH REL
		TWA (total)	10 mg/m ³	NIOSH REL
		TWA (Respirable)	5 mg/m ³	NIOSH REL
		TWA (total)	10 mg/m ³	NIOSH REL
		TWA (Respirable)	5 mg/m ³	NIOSH REL
		TWA (total)	10 mg/m ³	NIOSH REL
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Total)	15 mg/m ³	OSHA P0
		TWA (Respirable fraction)	5 mg/m ³	OSHA P0
aluminium hydroxide	21645-51-2	TWA (Total dust)	15 mg/m ³	OSHA P0
		TWA (respirable dust fraction)	5 mg/m ³	OSHA P0
Carbon black	1333-86-4	TWA (Respirable particulate matter)	1 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	1 mg/m ³	ACGIH
Carbon black	1333-86-4	TWA	3.5 mg/m ³	ACGIH
		TWA	3.5 mg/m ³	OSHA Z-1
		TWA	3.5 mg/m ³	OSHA P0
		TWA (Inhalable particulate)	3 mg/m ³	ACGIH

SAFETY DATA SHEET
Foster® AIR-TIGHT™ FDS-181 BLACK

Version 1.1

Revision Date 03/28/2024

		matter)		
		PEL	3.5 mg/m ³	CAL PEL
Quartz (SiO ₂)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (total dust)	30 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m ³	CAL PEL
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.
 In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection

Material : Nitrile rubber
 Remarks : For prolonged or repeated contact use protective gloves.

Eye protection : Safety glasses

Protective measures : No special protective equipment required.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
 Color : black
 Odor : ammoniacal
 Odor Threshold : no data available
 Melting point/freezing point : 32 °F

SAFETY DATA SHEET**Foster® AIR-TIGHT™ FDS-181 BLACK**

Version 1.1

Revision Date 03/28/2024

Boiling point/boiling range	: 212 °F
Flash point	: Not applicable
Evaporation rate	: is not determined
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: Upper flammability limit is not determined
Lower explosion limit	: Lower flammability limit is not determined
Vapor pressure	: is not determined
Relative vapor density	: is not determined
Density	: 11.2 - 12.5 lb/gal
Solubility(ies)	
Water solubility	: dispersible
Partition coefficient: n- octanol/water	: no data available
Autoignition temperature	: is not determined

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Hazardous polymerization does not occur.
Hazardous decomposition products	: Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
---------------------	---

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

SAFETY DATA SHEET**Foster® AIR-TIGHT™ FDS-181 BLACK**

Version 1.1

Revision Date 03/28/2024

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Paraffin waxes and Hydrocarbon waxes, chloro :**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.0109 mg/l
Exposure time: 96 h
Test Method: flow-through test

Persistence and degradability

No data available

Bioaccumulative potential**Components:****Paraffin waxes and Hydrocarbon waxes, chloro :**

Partition coefficient: n- : log Pow: 7.46 - 11.48 (20 °C)
octanol/water pH: 7
GLP: no

Alkanes, C14-17, chloro :

Partition coefficient: n- : log Pow: 4.7 - 8.3
octanol/water GLP: no

Mobility in soil

No data available

SAFETY DATA SHEET**Foster® AIR-TIGHT™ FDS-181 BLACK**

Version 1.1

Revision Date 03/28/2024

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.
The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Alkanes, C14-17, Chloro)
Class : 9
Packing group : III
Labels : Miscellaneous,
Packing instruction (cargo aircraft) : 956
Packing instruction (passenger aircraft) : 956
Remarks : PACKAGES <5 L NOT REGULATED, IATA 4.4, SP A197

IMDG-Code

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(Alkanes, C14-17, Chloro)
Class : 9
Subsidiary risk : ENVIRONM.
Packing group : III
Labels : 9 (ENVIRONM.)
EmS Code : F-A, S-F
Marine pollutant : yes
Remarks : PACKAGES <5 L NOT REGULATED, IMDG 3.3 SP 969

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

SAFETY DATA SHEET**Foster® AIR-TIGHT™ FDS-181 BLACK**

Version 1.1

Revision Date 03/28/2024

49 CFR

Not regulated as a dangerous good

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**SARA 311/312 Hazards** : Reproductive toxicity**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

US State Regulations**California Prop 65** Please contact Supplier for more information.**The ingredients of this product are reported in the following inventories:**

TSCA All substances listed as active on the TSCA inventory
Inventories Legend TSCA (USA), DSL (Canada), REACH(Europe), AIIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

SAFETY DATA SHEET


Foster® AIR-TIGHT™ FDS-181 BLACK

Version 1.1

Revision Date 03/28/2024

Further information

NFPA:



HMIS III:

HEALTH	1/
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.