

Foster® AIR-TIGHT™ FDS-181 GRAY

Version 1.1 Revision Date 03/28/2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Foster® AIR-TIGHT™ FDS-181 GRAY

Product code : 100000013724

Manufacturer or supplier's details

Company : H.B. Fuller Construction Products

Address : 1105 South Frontenac

Aurora, IL, 60504

Telephone : 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Water based sealant

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Color	gray
Odor	ammoniacal

GHS Classification

Effects on or via lactation :

GHS label elements

Not a hazardous substance or mixture.

Potential Health Effects

Carcinogenicity:

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

Group 2B: Possibly carcinogenic to humans
Paraffin waxes and 63449-39-8



Foster® AIR-TIGHT™ FDS-181 GRAY

Revision Date 03/28/2024 Version 1.1

Hydrocarbon waxes, chloro

Alkanes, chloro 61788-76-9

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen

> Quartz (SiO2) 14808-60-7

Reasonably anticipated to be a human carcinogen Paraffin waxes and 63449-39-8

Hydrocarbon waxes, chloro

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
Limestone	1317-65-3	30 - 50
aluminium hydroxide	21645-51-2	10 - 20
Paraffin waxes and Hydrocarbon waxes, chloro	63449-39-8	5 - 10
Alkanes, chloro	61788-76-9	5 - 10
Alkanes, C14-17, chloro	85535-85-9	5 - 10
Quartz (SiO2)	14808-60-7	0.1 - 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Show this material safety data sheet to the doctor in

attendance.

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.

: Flush eyes with water at least 15 minutes. Get medical In case of eye contact

attention if eye irritation develops or persists.

: Do not induce vomiting. Seek medical attention if symptoms If swallowed

develop. Provide medical care provider with this SDS.

Most important symptoms and effects, both acute and

delayed

: May cause harm to breast-fed children.



Foster® AIR-TIGHT™ FDS-181 GRAY

Version 1.1 Revision Date 03/28/2024

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Not combustible.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: none

Specific hazards during fire

fighting

: Cool closed containers exposed to fire with water spray.

Specific extinguishing

methods

Further information

: This product is an aqueous mixture that will not burn. Dried

product film will burn in a fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Refer to protective measures listed in sections 7 and 8.

Environmental precautions : No special environmental precautions required.

Prevent product from entering drains.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : No special precautions are needed in handling this material.

Conditions for safe storage : Keep container closed when not in use.

Keep in a dry, cool place.

Materials to avoid : Do not freeze.

No special restrictions on storage with other products.

Storage temperature : $>= 40 \, ^{\circ}F$

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters



Foster® AIR-TIGHT™ FDS-181 GRAY

Version 1.1 Revision Date 03/28/2024

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA	5 mg/m3	NIOSH REL
		(Respirable)		
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total)	15 mg/m3	OSHA P0
		TWA (Respirable fraction)	5 mg/m3	OSHA P0
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
aluminium hydroxide	21645-51-2	TWA (Respirable particulate matter)	1 mg/m3	ACGIH
		TWA (Respirable particulate matter)	1 mg/m3	ACGIH
Quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWÁ	10 mg/m3	OSHA Z-3
		(respirable)	/ %SiO2+2	
		TWA	250 mppcf	OSHA Z-3
		(respirable)	/ %SiO2+5	
		TWA (Respirable fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable	0.05 mg/m3	OSHA Z-1



Foster® AIR-TIGHT™ FDS-181 GRAY

Version 1.1 Revision Date 03/28/2024

dust)		
PEL (Respirable dust)	0.05 mg/m3	CAL PEL
TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection

Material : Nitrile rubber

Remarks : For prolonged or repeated contact use protective gloves.

Eye protection : Safety glasses

Protective measures : No special protective equipment required.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Color : gray
Odor : ammoniacal

Odor Threshold : no data available

Melting point/freezing point : 32 °F Boiling point/boiling range : 212 °F

Flash point : Not applicable Evaporation rate : is not determined

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit : Upper flammability limit

is not determined

Lower explosion limit : Lower flammability limit

is not determined

Vapor pressure : is not determined
Relative vapor density : is not determined
Density : 11.2 - 12.5 lb/gal

Solubility(ies)

Water solubility : dispersible



Foster® AIR-TIGHT™ FDS-181 GRAY

Version 1.1 Revision Date 03/28/2024

Partition coefficient: n-

octanol/water

: no data available

Autoignition temperature : is not determined

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

Hazardous decomposition

products

: Hazardous polymerization does not occur.

: Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure



Foster® AIR-TIGHT™ FDS-181 GRAY

Version 1.1 Revision Date 03/28/2024

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Paraffin waxes and Hydrocarbon waxes, chloro:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.0109 mg/l

Exposure time: 96 h

Test Method: flow-through test

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Paraffin waxes and Hydrocarbon waxes, chloro:

Partition coefficient: n- : log Pow: 7.46 - 11.48 (20 °C)

octanol/water pH: 7 GLP: no

Alkanes, C14-17, chloro:

Partition coefficient: n- : log Pow: 4.7 - 8.3GLP: no

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : To the best of our knowledge, this product does not meet the

definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities

for more restrictive requirements.

The hazard and precautionary statements displayed on the

label also apply to any residues left in the container.



Foster® AIR-TIGHT™ FDS-181 GRAY

Version 1.1 Revision Date 03/28/2024

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Alkanes, C14-17, Chloro)

Class : 9 Packing group : III

Labels : Miscellaneous,

Packing instruction (cargo

aircraft)

Packing instruction : 956

(passenger aircraft)

Remarks : PACKAGES <5 L NOT REGULATED, IATA 4.4, SP A197

IMDG-Code

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

956

(Alkanes, C14-17, Chloro)

Class : 9

Subsidiary risk : ENVIRONM.

Packing group : III

Labels : 9 (ENVIRONM.)

EmS Code : F-A, S-F Marine pollutant : yes

Remarks : PACKAGES <5 L NOT REGULATED, IMDG 3.3 SP 969

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Reproductive toxicity



Foster® AIR-TIGHT™ FDS-181 GRAY

Version 1.1 Revision Date 03/28/2024

SARA 302 : This material does not contain any components with a section 302

EHS TPQ.

SARA 313 : This material does not contain any chemical components with known

CAS numbers that exceed the threshold (De Minimis) reporting levels

established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

US State Regulations

California Prop 65 Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:


TSCA All substances listed as active on the TSCA inventory Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AllC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

Further information





HMIS III:

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and



Foster® AIR-TIGHT™ FDS-181 GRAY

Version 1.1

Revision Date 03/28/2024

because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.