

Foster® AIR-TIGHT[™] FDS-181 GRAY

Version 1.0		Revision Date 12/21/2020
SECTION 1. PRODUCT AND C	OMP	ANY IDENTIFICATION
Product name	:	Foster® AIR-TIGHT™ FDS-181 GRAY
Product code	:	10000013724
Manufacturer or supplier'	s deta	ails
Company	:	H.B. Fuller Construction Products
Address	:	1105 South Frontenac Aurora, IL, 60504
Telephone	:	1-800-552-6225
Medical Emergency Phone	Num	per (24 Hours): 1-888-853-1758
Transport Emergency Phor	ne Nur	nber (CHEMTREC): 1-800-424-9300
Recommended use of the	chen	nical and restrictions on use
Recommended use	:	Water based sealant
Restrictions on use	:	For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Color	gray
Odor	ammoniacal

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Potential Health Effects

Carcinogenicity:

IARC

Group 1: Carcinogenic to humansDuring normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.

Quartz (SiO2)

14808-60-7



Foster® AIR-TIGHT™ FDS-181 GRAY				
Version 1.0	Revision Date 12/21/2020			
OSHA NTP	Group 2B: Possibly carcinogenic to humansDuring normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk. Paraffin waxes and 63449-39-8 Hydrocarbon waxes, chloro Alkanes, chloro 61788-76-9 titanium dioxide 13463-67-7 No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. Known to be human carcinogenDuring normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk. Quartz (SiO2) 14808-60-7 Reasonably anticipated to be a human carcinogenDuring normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.			

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
calcium carbonate	471-34-1	30 - 50
aluminium hydroxide	21645-51-2	10 - 20
Paraffin waxes and Hydrocarbon waxes, chloro	63449-39-8	5 - 10
Alkanes, chloro	61788-76-9	5 - 10
titanium dioxide	13463-67-7	0.1 - 1
Quartz (SiO2)	14808-60-7	0.1 - 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	: Show this material safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air.



Foster® AIR-TIGHT™ FDS-181 GRAY				
Version 1.0 Revision Date 12/21/2020				
	If symptoms persist, call a physician.			
In case of skin contact	: Wash off with soap and water.			
In case of eye contact	: Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.			
If swallowed	: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.			

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	 Not combustible. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	: none
Specific hazards during fire fighting	: Cool closed containers exposed to fire with water spray.
Specific extinguishing methods Further information	: This product is an aqueous mixture that will not burn. Dried product film will burn in a fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Refer to protective measures listed in sections 7 and 8.	
Environmental precautions	: No special environmental precautions required. Prevent product from entering drains.	
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).	

SECTION 7. HANDLING AND STORAGE

Materials to avoid	: Do not freeze.
Conditions for safe storage	: Keep container closed when not in use. Keep in a dry, cool place.
Advice on safe handling	: No special precautions are needed in handling this material.



Foster® AIR-TIGHT[™] FDS-181 GRAY

Version 1.0	Revision Date 12/21/2020

No special restrictions on storage with other products.

Storage temperature

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

: >= 40 °F

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
calcium carbonate	471-34-1	PEL (Total dust)	10 mg/m3	CAL PEL
		PEL (respirable dust fraction)	5 mg/m3	CAL PEL
aluminium hydroxide	21645-51-2	TWA (Respirable particulate matter)	1 mg/m3	ACGIH
		TWA (Respirable particulate matter)	1 mg/m3	ACGIH
titanium dioxide	13463-67-7	TWA	10 mg/m3	ACGIH
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total)	10 mg/m3	OSHA P0
		TWA (Total dust)	10 mg/m3	OSHA P0
Quartz (SiO2)	14808-60-7	TWÁ (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWÁ (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL	0.05 mg/m3	CAL PEL



Foster® AIR-TIGHT[™] FDS-181 GRAY

Version 1.0

Revision Date 12/21/2020

(Respirable dust)		
TWA	0.1 mg/m3	OSHA P0
(respirable		
dust fraction)		

Personal protective equipment

Respiratory protection	 No personal respiratory protective equipment normally required. In case of insufficient ventilation, wear suitable respiratory equipment.
Hand protection Material Remarks	: Nitrile rubber : For prolonged or repeated contact use protective gloves.
Eye protection	: Safety glasses
Protective measures	: No special protective equipment required.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Color Odor Odor Threshold	: liquid : gray : ammoniacal : No data available
Melting point/freezing point	: 32 °F
Boiling point/boiling range	: 212 °F
Evaporation rate Flammability (solid, gas)	is not determinedNot classified as a flammability hazard
Upper explosion limit	: Upper flammability limit is not determined
Lower explosion limit	: Lower flammability limit is not determined
Relative vapor density	: is not determined
Density Solubility(ies)	: 11.2 - 12.5 lb/gal
Water solubility	: dispersible
Partition coefficient: n- octanol/water	: No data available
Autoignition temperature	: is not determined



Foster® AIR-TIGHT[™] FDS-181 GRAY

Version 1.0

Revision Date 12/21/2020

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions Hazardous decomposition products	: Hazardous polymerization does not occur.
	: Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION



Foster® AIR-TIGHT[™] FDS-181 GRAY

Version 1.0

Revision Date 12/21/2020

Ecotoxicity

<u>Components:</u> Paraffin waxes and Hydrocarbon waxes, chloro :				
Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.0109 mg/l Exposure time: 96 h Test Method: flow-through test			
Persistence and degradability				
No data available Bioaccumulative potential				
Mobility in soil				
No data available				
Other adverse effects				
No data available				

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	 To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements. The hazard and precautionary statements displayed on the label also apply to any residues left in the container.
	label also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION

Special precautions for user

Not applicable

Domestic regulation

49 CFR

Not regulated as a dangerous good

International Regulations

IATA-DGR UN/ID No.

: 3077



Eastar® AID TICUTIN EDG 101 CDAV

Foster	® AIR-TIGHT™ FDS-181 GRAY
Version 1.0	Revision Date 12/21/2020
Proper shipping name	 Environmentally hazardous substance, solid, n.o.s. (ALKANES, C14-17, CHLORO)
Class	: 9
Subsidiary risk	: ENVIRONM.
Packing group	: 111
Labels	: 9 (ENVIRONM.)
Packing instruction (cargo aircraft)	: 956
Packing instruction (passenger aircraft)	: 956
IMDG-Code	
UN number	: 3077
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
	(ALKANES, C14-17, CHLORO)
Class	: 9
Subsidiary risk	: ENVIRONM.
Packing group	: 111
Labels	: 9 (ENVIRONM.)
EmS Code	: F-A, S-F
Marine pollutant	: no
·	

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards	:	No SARA Hazards
SARA 302	:	This material does not contain any components with a section 302 EHS TPQ.
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

US State Regulations



Foster® AIR-TIGHT™ FDS-181 GRAY

Version 1.0

Revision Date 12/21/2020


California Prop 65 Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories: TSCA All substances listed as active on the TSCA inventory Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AICS (Australia), NZIOC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Department - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

Further information



The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.