



82-55

Product Data Sheet

PROPERTIES

COLOR:

Tan

APPLICATION CONSISTENCY:

Trowel, Putty Knife, Caulking Gun

AVERAGE WEIGHT / U.S. GALLON (ASTM D1475):

8.8 lbs. (1.05 kg/l)

AVERAGE NON-VOLATILE (ASTM D2369):

64% by weight

COVERAGE RANGE:

500 – 1000 anchors per gallon

BONDING TIME RANGE:

Depends on temperature, humidity and application rate.

0 – 15 minutes

DRYING / SET TIME:

Depends on temperature, humidity and application rate.

24 hours to 72 hours

SERVICE TEMPERATURE LIMITS:

Temperature at coated surface.

-20°F to 250°F (-29°C to 121°C)

FLAMMABILITY:

1°F (-17°C)

VOC Content (Average):

368 g/l – less exempt solvent

™ Trademark of H.B. Fuller Construction Products Inc.

Visit us on the web at www.fosterproducts.com

FOSTER INSULATION HANGER / STICK PIN ADHESIVE

FOSTER® HANGER/PIN ADHESIVE is a solvent based, high strength, high body adhesive designed for adhering metal and nylon insulation anchors/pins/hangers to metal ducts, walls, concrete and masonry surfaces. It dries quickly and provides a strong bond that will withstand thermal cycling.

Foster 82-55 Adhesive may be used for other general purpose construction applications where a high strength solve adhesive is desired

APPLICATION

For industrial use only. This product should be applied by trained and qualified craftspeople. Make sure surfaces are clean and dry and free of oils or other contaminants before application.

Using a putty knife apply a 1/16" film or dab the size of a small walnut of adhesive to the base of the hanger. Immediately press the hanger in place with a slight twisting motion to ensure full contact is made with adhesive between the hanger and surface. Adhesive should extrude through the holes in the hanger surface and fully cover the entire hanger base.

Allow 24-72 hours for the adhesive to fully dry and develop full strength. Do not apply a load to the hanger before it is fully set.

LIMITATIONS

Store and apply between 40°F (4°C) and 100°F (38°C).

New concrete must be allowed a full 28 day cure before bonding hangers to the surface to ensure best adhesion. Concrete may need to be pressure washed to remove any surface curing agents or other contaminants that may interfere with adhesion.

Always test plastic materials for compatibility before use.

Ensure the product is completely dry and free of any solvent odors if food is involved.

IMPORTANT: H.B. Fuller Construction Products Inc. warrants that each of its products will be manufactured in accordance with the specifications in effect on the date of manufacture. WE MAKE NO OTHER WARRANTIES AND EXPRESSLY DISCLAIM ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a product fails to meet this limited warranty, purchaser's sole and exclusive remedy is replacement of the product or, at our option, refund of the purchase price. OUR ACCEPTANCE OF ANY ORDERS FOR THE PRODUCT IS EXPRESSLY CONDITIONAL UPON PURCHASER'S ASSENT TO THE TERMS ON THE APPLICABLE INVOICE. R0423

ADEQUATE TESTS: The information contained herein we believe is correct to the best of our knowledge and tests. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that adequate tests be performed by you to determine if this product meets all of your requirements. The warranted shelf life of our products is twelve months from date of shipment to the original purchaser or as otherwise provided on the certificate of analysis.

For professional use only. Keep out of reach of children.
Consult Safety Data Sheet and container label for further information.

H.B. Fuller Construction Products Inc.

1105 South Frontenac Street o Aurora, IL 60504 o 800-832-9002 o fax 800-952-2368