

PROPERTIES

COLOR:

Gray

FORM:

Malleable Extruded Butyl Tape

Range of sizes and lengths available including:
1/8" x 1" x 50 ft (3.2 mm x 25 mm x 15.2m)

SERVICE TEMPERATURE (ASTM C1257):

-40°F to 190°F (-40°C to 88°C)

APPLICATION TEMPERATURE (ASTM C603):

20°F to 120°F (-7°C to 49°C)

SOLIDS CONTENT / SHRINKAGE (ASTM C681 / C771):

100% solids / No shrinkage

VOC CONTENT (ASTM D3960):

0%

SHORE A HARDNESS (ASTM C661)

20 @77°F (25°C)

LOW TEMPERATURE FLEXIBILITY (ASTM C765):

Flexible at -20°F (-29°C)

VEHICLE MIGRATION (ASTM C772):

No staining

YIELD STRENGTH (ASTM C908)

6 psi - minimum

LIMITATIONS

Store between 20°F – 90°F (-7°C – 32°C).

Shelf life: 24 months minimum

Do not apply to damp, frosty or contaminated surfaces.

Confirm adhesion with intended substrates prior to application

Not for structural bonding. Requires mechanical fastening or stabilized joints to prevent substrate movement.


Butyl Flashing Tape

Foster® 96-04 Butyl Flashing Tape is an extruded pre-formed, double sided tape furnished in rolls between release liner. It is non-hardening, solvent free, 100% solids gap filling sealant with excellent tack. It forms a weather resistant and water tight seal with strong adhesion to various substrates including metal, wood, glass, rubber and masonry.

96-04 Butyl Flashing Tape will deform under pressure to seal laps in metal jacketing when banded in place. May also be used to seal butt joints in rigid cellular glass or other foam insulations or fill voids to create water tight seal.

May be used to seal butyl rubber sheet to the insulation or vapor retarder surface under banding over contraction joints in cryogenic insulation applications.

As a butyl tape there is no required cure or dry time so joints can be closed and sealed immediately.



TM Trademark of H.B. Fuller Construction Products Inc.

Visit us on the web at fosterproducts.com

H.B. Fuller Construction Products Inc.

6107 Industrial Way ○ Houston, TX 77011 ○ 833-849-3700

APPLICATION GUIDE FOR FOSTER® 96-04 Butyl Flashing Tape

PREPARATION

Apply only to clean, dry, oil-free surfaces. Surfaces must be free of frost and water. Dirt, dust and loose insulation must be removed prior to application

APPLICATION

Do not overlap tape to join, always butt ends without stretching to avoid creating a high spot in the sealant.

For sealing metal jacketing apply the tape to the longitudinal lap and around the abutting circumferential lap. Leave the release liner in place until the jacket is ready to be installed to avoid contamination. Remove release liner on the circumferential sealant tape and place metal jacket in place making contact with the circumferential lap on the leading edge and making its way around to the open longitudinal lap. Press firmly in place making complete contact with both surfaces to the sealant. Then, lifting the lap slightly, remove the release liner from longitudinal overlap. Band jacketing in place putting pressure between laps to create the seal. All metal jacketing shall be installed to be water shedding over the sealed joints.

On insulation joints place sealant on the butt joint and then tightly press the adjoining insulation in place compressing sealant tape slightly to ensure a tight seal. Band or tape insulation in place under slight compression to ensure full and tight seal.

CLEAN-UP

No assembly application clean up required. If disassembly is desired, the butyl glazing tape may be removed from non-aged assemblies by grasping the butyl tape and rapidly (in a snapping motion) pulling it from the substrate surface. Any residual butyl material may be removed from the hardest surfaces with a 50/50 isopropyl alcohol/water solution. DO NOT USE SOLVENTS such as mineral spirits or paint thinners.

CUSTOMER SERVICE: (833) 849-3700

IMPORTANT: H.B. Fuller Construction Products Inc. warrants that each of its products will be manufactured in accordance with the specifications in effect on the date of manufacture. WE MAKE NO OTHER WARRANTIES AND EXPRESSLY DISCLAIM ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a product fails to meet this limited warranty, purchaser's sole and exclusive remedy is replacement of the product or, at our option, refund of the purchase price. OUR ACCEPTANCE OF ANY ORDERS FOR THE PRODUCT IS EXPRESSLY CONDITIONAL UPON PURCHASER'S ASSENT TO THE TERMS ON THE APPLICABLE INVOICE.

ADEQUATE TESTS: The information contained herein we believe is correct to the best of our knowledge and tests. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that adequate tests be performed by you to determine if this product meets all of your requirements. The warranted shelf life of our products is twelve months from date of shipment to the original purchaser or as otherwise provided on the certificate of analysis.

For professional use only.