



FOS-STIK™ 85-40

Adhesive spray featuring clean, consistent, high-strength bonding for mechanical insulation installation

UP TO
1,075 ft²
Coverage
per Canister



Strong, Versatile Adhesion



Flexible Installation Window



Clean Web Spray Pattern



One-Way or Two-Way Bonding





FOS-STIK™ 85-40 Canister Adhesive Spray

FOS-STIK™ 85-40 is a professional-grade web-spray adhesive designed for fast, consistent application across mechanical insulation installations. It delivers clean spray performance, strong bonding, and excellent compatibility—including use on polystyrene.

PERFORMANCE HIGHLIGHTS

- **Dependable bonding performance** on insulation, metals, wood, and polystyrene
- **Flexible working window**
60 minute open time for insulation attachment.
(Avoid dust contamination)
- **High-efficiency coverage**
delivering up to 1,075 ft² per canister to reduce change-outs and improve productivity
- **Clean, controlled spray pattern**
that helps maintain tidy and professional job sites
- **Adaptable bonding capability**
supporting both quick-tack and stronger permanent applications

APPLICATIONS

- HVAC insulation installation
- Duct liner and duct wrap
- Insulation boards (including polystyrene)
- Custom insulation fabrication
- General interior assembly requiring clean, adjustable bonding

KEY TECHNICAL DATA

Color	Clear
Spray Pattern	Web spray
Coverage	1,075 ft ² per canister
Bonding Time	0 to 60 mins
Application Method	Canister spray system
Gross Weight	40 lbs

Foster® adhesives are engineered to help contractors work faster, cleaner, and more confidently. With excellent insulation compatibility and a high-efficiency spray pattern, FOS-STIK™ 85-40 delivers performance you can trust on every installation.

3068-R0326

